

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/8

Chemdur Gloss Clear Hardener

Revision 1
Revision date 2015-06-03

SECTION 1: Identification of	SECTION 1: Identification of the substance/mixture and of the company/undertaking				
1.1. Product identifier	1.1. Product identifier				
Product name	oduct name Chemdur Gloss Clear Hardener				
1.2. Relevant identified uses of	of the substance or mixture and uses advised against				
Description	Restricted to professional users.				
	Component Of A Two Pack Polyurethane Floor Coating.				
1.3. Details of the supplier of	the safety data sheet				
Company	Virtus Resins				
Address	The Shippon, Faenol				
	Pentrecelyn				
	Ruthin				
	LL15 2SP				
Web	www.epoxyresinsuppliers.co.uk				
Telephone	+44 (0)1978 790 744				
Fax					
Email	info@epoxyresinsuppliers.co.uk				
Email address of the	info@ epoxyresinsuppliers.co.uk				
competent person					
1.4. Emergency telephone nu	mber				
Emergency telephone	+44 (0)1978 790 744				
number					
	8.30am to 5.00pm Mon - Fri				

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification -	Xn; R20 Xi; R37-43 R10
1999/45/EC	Symbols: Xn: Harmful.
Main hazards	Flammable. Harmful by inhalation. Irritating to respiratory system. May cause sensitisation by skin contact.
0.4.0. Olassification. E	
2.1.2. Classification - E	Flam. Liq. 3: H226; Skin Irrit. 2: H315; Skin Sens. 1: H317; Acute Tox. 4: H332;
1272/2008	

2.2. Label elements

Hazard pictograms





Signal Word

Hazard Statement

Warning

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.



Revision 1 Revision date 2015-06-03

2.2. Label elements	
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	Acute Tox. 4: H332 - Harmful if inhaled.
Precautionary Statement:	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
Prevention	smoking.
	P233 - Keep container tightly closed.
	P240 - Ground/bond container and receiving equipment.
	P241 - Use explosion-proof electrical/ventilating/lighting// equipment.
	P242 - Use only non-sparking tools.
	P243 - Take precautionary measures against static discharge.
	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264 - Wash thoroughly after handling.
	P271 - Use only outdoors or in a well-ventilated area.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .
Response	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell.
	P321 - Specific treatment (see on this label).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement:	P403+P235 - Store in a well-ventilated place. Keep cool.
Storage	
Precautionary Statement:	P501 - Dispose of contents/container to
Disposal	

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
aliphatic polyisocyanate		28182-81-2				Xn; R20 Xi; R37-43	
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	607-195-00-7	108-65-6	203-603-9			R10	
Xylene (Xylene, o-,m-,-p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7			R10 Xn; R20/21 Xi; R38	
Ethylbenzene	601-023-00-4	100-41-4	202-849-4			F; R11 Xn; R20	
Hexamethylene-di-isocyanate	615-011-00-1	822-06-0	212-485-8			T; R23 Xi; R36/37/38 R42/43	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
aliphatic polyisocyanate		28182-81-2				Skin Sens. 1: H317; Acute Tox. 4: H332;	
Xylene (Xylene, o-,m-,-p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7			Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;	
Ethylbenzene	601-023-00-4	100-41-4	202-849-4			Flam. Liq. 2: H225; Acute Tox. 4: H332;	
Hexamethylene-di-isocyanate	615-011-00-1	822-06-0	212-485-8			Acute Tox. 3: H331; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317;	

SECTION 4: First aid measures



Revision 1 Revision date 2015-06-03

41	Description	of first aid	measures

4.1. Description of first aid me	easures
Inhalation	Keep patient calm, remove to fresh air, seek medical attention.
Eye contact	Immediately wash affected eyes for at least 15 minutes under running water with eyelids help open, consult an eye specialist.
Skin contact	After contact with skin, wash immediately with plenty of water and soap.
Ingestion	DO NOT induce the patient to vomit, medical advice is required.
4.2. Most important symptom	s and effects, both acute and delayed
Inhalation	Seek medical attention if irritation or symptoms persist.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.
4.3. Indication of any immedia	ate medical attention and special treatment needed
Inhalation	Seek medical attention.
Eye contact	Seek medical attention.
Skin contact	Seek medical attention.
Ingestion	Seek medical attention.
SECTION 5: Firefighting me	easures
5.1. Extinguishing media	
	Carbon dioxide (CO2). Foam.
5.2. Special hazards arising fr	
1 0	Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen, isocyanate vapors
	and traces of hydrogen cyanide. In the event of fire and/or explosion do not breathe fumes.
5.3. Advice for firefighters	
	Special protective equipment. Wear self-contained breathing apparatus and chemical-protective clothing. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.
SECTION 6: Accidental rele	pase measures
	otective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective clothing.
6.2. Environmental precaution	ns
	Do not allow runoff water to enter sewers or drains. Do not let product contaminate subsoil.
6.3. Methods and material for	containment and cleaning up
	Remove mechanically; cover the remainder with wet, absorbant material (e.g sawdust, chemical bindr based on calcium silicate hydrate, sand). After approx. one hour transfer to waste container and do not seal. (evolution of CO2!). Keep damp in a safe ventilated area for several days. For further disposal measures see chapter 13.
6.4. Reference to other sectio	ns
	Information regarding exposure controls/personal protection and disposal
	considerations can be found in section 8 and 13.
SECTION 7: Handling and	storage
7.1. Precautions for safe hand	lling
	Ensure adequate ventilation of the working area.
7.2. Conditions for safe storage	ge, including any incompatibilities



Keep container dry and tightly closed in a cool and well ventilated place.

7.3. Specific end use(s)

Revision 1 Revision date 2015-06-03

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Are listed on the following items according to where it is going to be used.

8.1.1. Exposure Limit Values

2-methoxy-1-methylethyl acetate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 274
(1-Methoxypropylacetate)		
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 548
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Ethylbenzene	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m3: 441
	WEL 15 min limit ppm: 125	WEL 15 min limit mg/m3: 552
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Hexamethylene-di-isocyanate	WEL 8-hr limit ppm:	WEL 8-hr limit mg/m3: 0.02
	WEL 15 min limit ppm:	WEL 15 min limit mg/m3:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Xylene (Xylene, o-,m-,-p-or	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
mixed isomers)		
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls





Ensure adequate ventilation of the working area.



8.2.1. Appropriate engineering controls Eye / face protection

Wear eye/face protection.

Skin protection - Handprotection

Wear suitable gloves.

Skin protection - Other

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



Revision 1 Revision date 2015-06-03

9.1. Information on basic physical and chemical properties

Solubility No data available

Appearance Liquid Colour Yellowish Odour smell of solvent pH Not determined Melting point No data available Freezing Point No data available Initial boiling point = 145 Flash point 38 Evaporation rate No data available Flammability (solid, gas) Not applicable. Vapour pressure No data available Vapour density No data available Relative density No data available Fat Solubility No data available Partition coefficient Not determined Autoignition temperature Not applicable. Viscosity No data available Explosive properties No data available Oxidising properties Not determined

9.2. Other information

	Conductivity	No data available
	Surface tension	No data available
	Gas group	No data available
	Benzene Content	No data available
١	Lead content	No data available
	VOC (Volatile organic	
	compounds)	

compounds)	compounds)					
SECTION 10: Stability and reactivity						
10.1. Reactivity	10.1. Reactivity					
	Water.					
10.2. Chemical stability						
	No data is available on this product.					
10.3. Possibility of hazardous	reactions					
	Amines. Alcohols.					
10.4. Conditions to avoid						
	No data is available on this product.					
10.5. Incompatible materials						
	No data is available on this product.					
10.6. Hazardous decomposition products						
	No hazardous decomposition products if stored and handled as prescribed/indicated.					
SECTION 11: Toxicological information						
11.1. Information on toxicological effects						

No data is available on this product.

No data is available on this product.

Serious eye damage/irritation No data is available on this product.

Acute toxicity

Skin corrosion/irritation

Revision 1 Revision date 2015-06-03

	Novicien auto 2010 00 00
11.1. Information on toxicolog	gical effects
Respiratory or skin sensitisation	No data is available on this product.
Germ cell mutagenicity	No data is available on this product.
Carcinogenicity	No data is available on this product.
Reproductive toxicity	No data is available on this product.
SECTION 12: Ecological in	formation
12.2. Persistence and degrada	ability
	No data is available on this product.
12.3. Bioaccumulative potent	ial
	No data is available on this product.
Partition coefficient	
	Chemdur Gloss Clear Not determined 2-methoxy-1-methylethyl acetate No data available Hardener
12.4. Mobility in soil	
	No data is available on this product.
12.5. Results of PBT and vPvl	·
	No data is available on this product.
12.6. Other adverse effects	100 data to distance on the product
	No data is available on this product.
SECTION 13: Disposal con	
13.1. Waste treatment method	
	Dispose in accordance with applicable international, national and local laws,
	ordinances and satutes.
	For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
	After final product withdrawel, all residues must be removed from containers (drip-free, powder-
	free or paste-free). Once the product residues adhering to the walls of the containers have been
	rendered harmless, teh product and hazard labels must be invalidated. Containers must be
	recycled in compliance with national legislation and environmental regulations.
SECTION 14: Transport inf	ormation
Hazard pictograms	
	3
14.1. UN number	•
	UN1866
14.2. UN proper shipping nam	ne
	RESIN SOLUTION
14.3. Transport hazard class(
ADR/RID	3
Subsidiary risk	1 -
	1



Revision 1 Revision date 2015-06-03

14.3. Transport hazard class(14.3. Transport hazard class(es)			
IMDG	3			
Subsidiary risk	-			
IATA	3			
Subsidiary risk	-			
14.4. Packing group				
Packing group	III			
14.5. Environmental hazards				
Environmental hazards	No			
Marine pollutant	No			
ADR/RID				
Hazard ID	30			
Tunnel Category	(D/E)			
IMDG				
EmS Code	F-E S-E			
IATA				
Packing Instruction (Cargo)	366			
Maximum quantity	220 L			
Packing Instruction	355			
(Passenger)				
Maximum quantity	60 L			
CECTION 45. Demiletem:	farmation.			

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

"COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC".

"REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC".

SECTION 16: Other information

Revision	This document differs from the previous version in the following areas:. 14 - ADR/RID. 14 - IMDG. 14 - IATA.
Text of risk phrases in	R10 - Flammable
Section 3	R11 - Highly flammable.
	R20/21 - Harmful by inhalation and in contact with skin.
	R20 - Harmful by inhalation.
	R23 - Toxic by inhalation.
	R36/37/38 - Irritating to eyes, respiratory system and skin.
	R37 - Irritating to respiratory system.
	R38 - Irritating to skin.

Revision 1 Revision date 2015-06-03

Other information	
	R42/43 - May cause sensitisation by inhalation and skin contact. R43 - May cause sensitisation by skin contact.
Text of Hazard Statements in Section 3	Skin Sens. 1: H317 - May cause an allergic skin reaction. Acute Tox. 4: H332 - Harmful if inhaled. Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 3: H331 - Toxic if inhaled. Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. STOT SE 3: H335 - May cause respiratory irritation.
General information	
	This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

