

# Zip Tudor™

Over-Sink or Under-Sink Water Heaters


**Open outlet to single point  
5.0 litre, 10.0 litre**



**Optional accessories**



UB1  
Monobloc mixer



TS1  
Telescopic 300-600 mm spout

**Features**

- Adjustable temperature control
- Choice of 5 or 10 litres capacity
- Over-sink models supplied complete with spout and valve
- Under-sink models for connection to open-outlet tapware only
- Mains cable connected
- CFC – free insulation
- Impact resistant, easy clean, white plastic casing
- Manually re-settable cutout
- Neon power indicator light

*As Zip policy is one of continuous product improvement, changes to specifications may be made without prior notice.*

*The terms Zip and Tudor are Trademarks*

# Zip Tudor™

## Over-Sink or Under-Sink Water Heaters

Zip Model	Product Code	Thermal Loss kWh/day	Weight (kg)		Dimensions (mm) H x W x D
			Empty	Full	
Zip Tudor™ Over-Basin	P4/52	0.32	3.5	8.5	390 x 225 x 215
Zip Tudor™ Under-Basin	P4/52UB	0.32	3.5	8.5	390 x 225 x 215
Zip Tudor™ Over-Basin	P4/102	0.40	4.0	14.0	455 x 310 x 265
Zip Tudor™ Under-Basin	P4/102UB	0.40	4.0	14.0	455 x 310 x 265

### Technical Features

- Over-sink or under-sink water heaters
- Open outlet to single point
- Swivel arm open outlet spout and on/off valve (over-sink models)
- Plumbing connections at top of heater (under-sink models)
- Full external temperature control ranging from 35°C to 80°C
- Frost protection setting to protect the heater when not in use
- Low watts density spiral heating element for rapid recovery and long life
- Manually re-settable over-temperature safety cut-out
- External neon light indicator to indicate when element is 'ON'
- Mains cable connected

**Capacity**  
5 litres, 10 litres

**Rating**  
2.0 kW

**Heating element**  
Embedded rod type

**Thermostat**  
Capillary type, adjustable 35°C to 80°C

**Water tank**  
Approved polypropylene tested to 40 psi

**Case**  
Impact resistant plastic.

**Insulation**  
Compressed high temperature insulation panels  
Contoured polyurethane, CFC free.

**Safety feature**  
Manually re-settable over-temperature safety cut-out.

**Approvals**  
WRAS approved and CE endorsed.

**Simple to install**  
Supplies hot water to a single outlet.

Connects directly to the cold water supply.  
No need for expansion vessel or relief valve.

**Simple to operate**  
Temperature controlled water whenever you want it.  
Externally adjustable temperature control.

Neon light indicates when heating element is 'ON'.

**Special safety features**  
Open-outlet non-pressurised system.

Frost protection setting protects heater when not in use.

Manually re-settable over-temperature safety cut-out.

**Warranty**  
One-year on site parts and labour.  
For full details of the Zip Warranty Scheme visit:  
[www.zipheaters.co.uk/warranty](http://www.zipheaters.co.uk/warranty).

### Installation

**Location**  
All models should be wall mounted.  
Screws and plugs suiting most walls provided.

**Plumbing**  
Can be connected to a rising main or to a cistern with a minimum working head of 5 metres.

All water connections are via 15mm compression fittings.

Over-sink models are supplied with a 300mm open outlet spout and water control valve.

Under-sink models must be installed only with a Zip-approved open-outlet tap.

Over-sink and under-sink models are NOT interchangeable.

**Electrical**  
To be wired to a double pole fused spur, minimum break rating of 13 amps.

Installation must comply with current IEE regulations.

**Caution**  
Variable temperature water heaters should be set only in strict compliance with regulations governing the temperature of stored and dispensed hot water.

**Technical Support**  
Contact Zip on: 0845 6 005 005

**Maintenance**  
Zip HydroCare Tel: 0845 6 005 005

### Dimensions

