

borg&
overström

U2



Unrivalled Performance

Solidly practical and visually striking, this innovative range brings a high capacity refreshment solution to any Horeca environment.



Power Requirements

Hertz 50/Volts 230

Max power consumption

Cold, Ambient & Sparkling 400W

Cold & Ambient 150W

Cold Temperature

Min 2°C /Max 11°C

Throughput litres per hour

Cold 60

Dimensions

Undercounter

Tap Dimensions

Dispense Height

WxDxH

262x450x485mm

220x250x470mm

285mm

Key Features

- Robust, solid build quality
- Simple to operate and maintain
- Available in ambient, chilled and sparkling
- Aesthetically striking
- Compact undercounter unit
- High capacity output

Available accessories

- Sanitisation Kit
- Install Kit with Filter
- Sparkling Refill (CO₂E290) (600g)
- CO₂ Regulator with Gauge
- Large Drip Tray
- Blue Tint Cups (7oz)



Water options



Chilled



Ambient



Sparkling

Configuration



Undercounter

Recommended environment



Offices



Hospitality



Leisure

Number of users



11 – 25



25+

u2 Models

Direct Chill, Complete Undercounter System, Chilled & Ambient - 601350

Direct Chill, Complete Undercounter System, Chilled & Sparkling - 601380

Direct Chill, Complete Undercounter System, Chilled, Ambient & Sparkling - 601390

Water system



Direct Chill

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Phone
+44 (0)1362 695 006
Email
sales@borgandoverstrom.com

borgandoverstrom.com

Ref: 838145
Version: 22102014