## Milwaukee Power Tools (MILM18BOS0)

## M18 B0S125-0 Random Orbital Sander 18V Bare Unit

The Milwaukee M18 BOS125 Random Orbital Sander delivers 14,000 to 24,000 sanding strokes per minute for faster material removal. The variable speed wheel features 6 speed settings, allowing the correct speed to be set for different types of material. The universal hook and loop sanding pad allows easy changing of sanding discs. REDLINK overload protection electronics in tool and battery pack deliver best in class system durability. REDLITHIUM-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life. Supplied with a dust extraction box, fitted with an internal filter that helps keep dust contained and managed. It also comes with a vacuum adaptor that fits all Milwaukee dust extractors. M18 BOS125-502B: 2 x 18V 5.0Ah Li-ion Batteries M18 BOS125-0: Bare Unit, No Battery or Charger Specification: Oscillating Speed: 14,000-24,000/min. Oscillating Diameter: 2.4mm Sanding Pad Size: 125mm The Milwaukee M18 BOS125-0 Random Orbital Sander is supplied as a bare unit, no battery or charger supplied.





Voltage	Input Power (Battery)	-	-
18V	Bare Unit	-	-