

## Company Profile



Via E. Majorana, 2 - 4  
Montecchio Emilia, Italy



Website



**Dieci Equipment Africa (Pty) Ltd**

Unit 11, Acacia Park  
1 Falcon Road, Durban  
Ballito, KZN, 4420

Tel: 032 947 0170

Email: [info@dieci.africa](mailto:info@dieci.africa)

Web: [www.dieci.africa](http://www.dieci.africa)



Dieci Equipment Africa (Pty) Ltd is the exclusive and sole distributor of Dieci telescopic forklifts in Southern Africa and imports the equipment directly from Dieci s.r.l. in Italy. The company also distributes it's own brand of conventional and rough terrain forklift trucks, which is know as DLift.

The owners have been involved in the lifting equipment sector since 2006 which began as a dealership for Manitou in the Rustenburg area, serving the very demanding Mining sector in the Platinum belt. With extreme emphasis always placed on quality after-sales support, the business expanded rapidly.

Dieci s.r.l. started out in 1962 by designing and building concrete mixers and in 1983 we were one of the first European manufacturers to develop and produce a range of telehandlers. The offering has continued to expand over the years: in 1998 Dieci presented the S.I.R. telehandler series – Samson, Icarus and Runner.

In 2000 they unveiled the now well-known Pegasus family of telehandlers with 360- and 400-degree rotating boom. More recently we launched HERCULES, the new line of high load capacity vehicles for heavy industry, as well as the AGRI PLUS and AGRI TECH vehicles, which are specially designed for intensive agricultural use. Added to this is the Agri Pivot range of wheel loaders with telescopic boom.

The result of this constant commitment is an offering that includes no fewer than 143 current production models. Furthermore, the state-of-the-art DIECI technical department provides customised solutions developed from standard vehicles based on customers’ specific technical requirements, in order to meet their special application needs.

**B-BBEE Level 2 Company.**



# Warranty

## 36 Month / 3000 Hour Warranty

All new Dieci Telehandlers sold in South Africa comes standard with 36 Month or 3000 Hour (whichever is the earliest) Dieci Care Gold Factory Warranty\*

The following parts are covered by the Warranty:

**Diesel Engine**

Crankcase, Cylinder head, Crankshaft, Camshaft, Connecting rods, Pistons, Turbo, Water pump, Bearings, Cylinder head gasket, Rocker arms, Valves, Springs and Guides, Oil pump, Fuel pump, Starter and Alternator.

**Transmission**

Hydrostatic pump and motor, Powershift transmission, Gearbox and Gears.

**Axles and Drives**

Conical gear wheel, differential, transmission shafts, gears and reduction gears.

**Electrical System**

Wiper motors, Dashboard, Hour meter, Electronic cards and Sensors.

**Cooling System**

Water pump, Thermostat, Water and oil radiator.

**Hydraulic System**

Hydraulic distributor, Accumulators, Hydraulic tank, Cylinders (excluding Seals), Iron piping and Pumps.

**Steering System**

Accumulator, Steering pump and Steering Cylinders (excluding Seals).

**Chassis and Arms**

Chassis, Axes, Boom, Stabilizers, Levers and ROPS/FOPS structure.

\*Terms and Conditions Apply






Material Handling





# Agriculture Range



	MINI AGRI 25.6	AGRI FARMER 30.7	AGRI STAR 37.7	AGRI STAR 38.10	AGRI PLUS 40.7 PS EV02
Engine	Kubota	Kubota	FPT	FPT	FPT
Nominal power	55,4 kW (74 HP)	73,4 kW (98 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)
Maximum speed	30 km/h (18,6 mph)	35 km/h (21,7 mph)	40 km/h (18,6 mph)	40 km/h (18,6 mph)	40 km/h (24,9 mph)
Maximum Capacity	2500 kg (5512 lb)	3000 kg (6614 lb)	3700 kg (8157 lb)	3800 kg (8378 lb)	4000 kg (8818 lb)
Maximum lifting height	5,78 m (19 ft)	6,35 m (20,8 ft)	7,35 m (24,1 ft)	9,75 m (32 ft)	7,00 m (23 ft)
Length	4125 mm (162,4 in)	4765 mm (187,6 in)	4950 mm (194,9 in)	4950 mm (194,9 in)	5075 mm (199,8 in)
Width	1850 mm (72,8 in)	2000 mm (78,7 in)	2290 mm (90,2 in)	2290 mm (90,2 in)	2260 mm (89 in)
Height	1950 mm (76,8 in)	2220 mm (87,4 in)	2310 mm (90,9 in)	2310 mm (90,9 in)	2445 mm (96,3 in)
Total weight (empty)	4900 kg (10803 lb)	6100 kg (13448 lb)	7500 kg (16535 lb)	7900 kg (17417 lb)	7700 kg (16976 lb)
Tyres	12x16,5"	400/70x20"	400/70x20"	400/70x20"	400/70x24"









# Construction and Mining Range



Engine  
Nominal power  
Maximum speed  
Maximum Capacity  
Maximum lifting height  
Length  
Width  
Height  
Total weight (empty)  
Tyres

APOLLO 25.6	DEDALUS 30.7	DEDALUS 30.9	ZEUS 37.7	SAMSON 45.8	ZEUS 38.10	ZEUS 33.11	ICARUS 40.14	ICARUS 40.17	ICARUS 55.17
Kubota	Kubota	Kubota	FPT	FPT	FPT	FPT	FPT	FPT	FPT
55,4 kW (74 HP)	73,4 kW (98 HP)	73,4 kW (98 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)	93 kW (125 HP)
30 km/h (18,6 mph)	35 km/h (21,7 mph)	35 km/h (21,7 mph)	30 km/h (18,6 mph)	30 km/h (18,6 mph)	30 km/h (18,6 mph)	40 km/h (24,9 mph)	35 km/h (21,7 mph)	35 km/h (21,7 mph)	30 km/h (18,6 mph)
2500 kg (5512 lb)	3000 kg (6614 lb)	3000 kg (6614 lb)	3700 kg (8157 lb)	4500 kg (9920 lb)	3800 kg (8378 lb)	3300 kg (7275 lb)	4000 kg (8818 lb)	4000 kg (8818 lb)	5450 kg (12015 lb)
5,78 m (19 ft)	6,35 m (20,8 ft)	8,70 m (28,5 ft)	7,35 m (24,1 ft)	7,90 m (25,1 ft)	9,75 m (32 ft)	10,60 m (34,8 ft)	13,40 m (44 ft)	16,60 m (54,5 ft)	17,03 m (55,9 ft)
4125 mm (162,4 in)	4765 mm (187,6 in)	4775 mm (188 in)	4950 mm (194,9 in)	4950 mm (194,9 in)	4950 mm (194,9 in)	5300 mm (208,7 in)	6200 mm (244,1 in)	6275 mm (247 in)	6580 mm (259,1 in)
1850 mm (72,8 in)	2000 mm (78,7 in)	2000 mm (78,7 in)	2290 mm (90,2 in)	2310 mm (90,9 in)	2310 mm (90,9 in)	2290 mm (90,2 in)	2360 mm (92,9 in)	2360 mm (92,9 in)	2440 mm (96,1 in)
1950 mm (76,8 in)	2220 mm (87,4 in)	2220 mm (87,4 in)	2310 mm (90,9 in)	2490 mm (98 in)	2310 mm (90,9 in)	2310 mm (90,9 in)	2500 mm (98,4 in)	2550 mm (100,4 in)	2570 mm (101,2 in)
4900 kg (10803 lb)	6100 kg (13448 lb)	6250 kg (13779 lb)	7600 kg (16755 lb)	8800 kg (19400 lb)	8000 kg (17637 lb)	8200 kg (18078 lb)	10900 kg (24030 lb)	12260 kg (27029 lb)	14000 kg (30865 lb)
12x16,5"	400/70x20"	400/70x20"	400/70x20"	400/70x20"	400/70x20"	400/70x20"	400/70x20"	400/70x24"	14.00x24"



Engine  
Nominal power  
Maximum speed  
Maximum Capacity  
Self-loading Shovel  
Concrete Yield  
Length  
Width  
Height  
Total weight (empty)  
Tyres

AB N 2400	AB N 2400 T	AB L 3500	AB L 3500 T	AB L 4700	AB L 4700 T	AB F 7000	AB F 7000 T
Lombardini	Lombardini	FPT	FPT	FPT	FPT	FPT	FPT
36,6 kW (49 HP)	36,6 kW (49 HP)	74 kW (99 HP)	74 kW (99 HP)	74 kW (99 HP)	74 kW (99 HP)	93 kW (125 HP)	93 kW (125 HP)
27 km/h (16,8 mph)	27 km/h (16,8 mph)	27 km/h (16,8 mph)	27 km/h (16,8 mph)	27 km/h (16,8 mph)	27 km/h (16,8 mph)	27 km/h (16,8 mph)	27 km/h (16,8 mph)
270 L (71,33 gal)	-	500 L (132,09 gal)	-	600 L (158,5 gal)	-	600 L (158,5 gal)	-
1,7 m³ (60 ft³)	1,7 m³ (60 ft³)	2,5 m³ (88 ft³)	2,5 m³ (88 ft³)	3,5 m³ (124 ft³)	3,5 m³ (124 ft³)	5,0 m³ (177 ft³)	5,0 m³ (177 ft³)
4495 mm (177 in)	4400 mm (173,2 in)	5030 mm (198 in)	4955 mm (195,1 in)	5520 mm (217,3 in)	5290 mm (208,3 in)	6475 mm (254,9 in)	6100 mm (240,2 in)
1960 mm (77,2 in)	1960 mm (77,2 in)	2370 mm (93,3 in)	2370 mm (93,3 in)	2400 mm (94,5 in)	2400 mm (94,5 in)	2370 mm (93,3 in)	2370 mm (93,3 in)
2755 mm (108,5 in)	2755 mm (108,5 in)	2915 mm (114,8 in)	2915 mm (114,8 in)	2940 mm (115,7 in)	2940 mm (115,7 in)	3075 mm (121,1 in)	3075 mm (121,1 in)
4000 kg (8818 lb)	4000 kg (8818 lb)	5900 kg (13007 lb)	5900 kg (13007 lb)	6700 kg (14771 lb)	6400 kg (14110 lb)	7400 kg (16314 lb)	7400 kg (16314 lb)
10.5x18"	10.5x18"	12.5x18"	12.5x18"	405/70x20"	405/70x20"	405/70x20"	405/70x20"



Engine  
Nominal power  
Maximum speed  
Maximum Capacity  
Dump body capacity (level)  
Dump body capacity (heaped )  
Total weight (empty)  
Length  
Width  
Height  
Tyres



DUMPER 1000 F	DUMPER 1000 T	DUMPER 1000 PA	DUMPER 4200	DUMPER 7000
Lombardini	Lombardini	Lombardini	FPT	FPT
15 kW (20 HP)	15 kW (20 HP)	15 kW (20 HP)	74 kW (99 HP)	93 kW (125 HP)
23 km/h (14,3 mph)	23 km/h (14,3 mph)	23 km/h (14,3 mph)	27 km/h (16,8 mph)	20 km/h (12,4 mph)
2500 kg (5512 lb)	2500 kg (5512 lb)	2500 kg (5512 lb)	8000 kg (17637 lb)	12000 kg (26455 lb)
1,0 m³ (35 ft³)	1,0 m³ (35 ft³)	1,0 m³ (35 ft³)	4,2 m³ (148 ft³)	7,0 m³ (247 ft³)
1,2 m³ (42 ft³)	1,2 m³ (42 ft³)	1,2 m³ (42 ft³)	5,3 m³ (187 ft³)	7,5 m³ (265 ft³)
1200 kg (2646 lb)	1300 kg (2866 lb)	1550 kg (3417 lb)	5000 kg (11023 lb)	6360 kg (14021 lb)
3100 mm (122 in)	3100 mm (122 in)	3100 mm (122 in)	4960 mm (195,3 in)	5790 mm (228 in)
1600 mm (63 in)	1600 mm (63 in)	1680 mm (66,1 in)	2350 mm (92,5 in)	2350 mm (92,5 in)
2520 mm (99,2 in)	2520 mm (99,2 in)	2520 mm (99,2 in)	3010 mm (118,5 in)	3090 mm (121,7 in)
7,5x16"	7,5x16"	7,5x16"	405/70x20"	405/70x20"



Engine  
Nominal power  
Maximum speed  
Maximum Capacity  
Maximum lifting height  
Length  
Width  
Height  
Total weight (empty)  
Tyres

PEGASUS 38.16 - 400"	PEGASUS 40.18 - 400"	PEGASUS 40.25	PEGASUS 50.19	PEGASUS 50.21	PEGASUS 60.16
Kubota	Kubota	FPT	FPT	FPT	FPT
73,4 kW (98 HP)	73,4 kW (98 HP)	104 kW (139 HP)	104 kW (139 HP)	104 kW (139 HP)	104 kW (139 HP)
25 km/h (15,5 mph)	25 km/h (15,5 mph)	40 km/h (24,9 mph)	40 km/h (24,9 mph)	40 km/h (24,9 mph)	40 km/h (24,9 mph)
3800 kg (8378 lb)	4000 kg (8818 lb)	4000 kg (8818 lb)	5000 kg (11023 lb)	5000 kg (11023 lb)	6000 kg (13228 lb)
15,70 m (51,5 ft)	18,00 m (59,1 ft)	24,10 m (79,1 ft)	18,70 m (61,4 ft)	20,50 m (67,3 ft)	15,70 m (51,5 ft)
6740 mm (265,4 in)	6630 mm (261 in)	8000 mm (315 in)	6800 mm (267,7 in)	7150 mm (281,5 in)	6720 mm (264,6 in)
2380 mm (93,7 in)	2380 mm (93,7 in)	2380 mm (93,7 in)	2380 mm (93,7 in)	2380 mm (93,7 in)	2380 mm (93,7 in)
3035 mm (119,5 in)	3035 mm (119,5 in)	3020 mm (118,9 in)	3020 mm (118,9 in)	3020 mm (118,9 in)	3020 mm (118,9 in)
13200 kg (29101 lb)	13700 kg (30203 lb)	17500 kg (38581 lb)	16500 kg (36376 lb)	17540 kg (38669 lb)	16600 kg (36597 lb)
400/70x20"	400/70x20"	18R22,5"	18R22,5"	18R22,5"	18R22,5"



Engine  
Nominal power  
Maximum speed  
Maximum Capacity  
Maximum lifting height  
Length  
Width  
Height  
Total weight (empty)  
Tyres



SAMSON 75.10	HERCULES 100.10	HERCULES 120.10	HERCULES 190.10	HERCULES 210.10	HERCULES 230.10
FPT	FPT	FPT	FPT	FPT	FPT
93 kW (125 HP)	104 kW (139 HP)	104 kW (139 HP)	129 kW (173 HP)	129 kW (173 HP)	129 kW (173 HP)
30 km/h (18,6 mph)	35 km/h (21,7 mph)	35 km/h (21,7 mph)	23 km/h (14,3 mph)	23 km/h (14,3 mph)	22 km/h (13,7 mph)
7500 kg (16535 lb)	10000 kg (22046 lb)	12000 kg (26455 lb)	19000 kg (41888 lb)	21000 kg (46297 lb)	23000 kg (50706 lb)
9,65 m (31,7 ft)	9,50 m (31,2 ft)	9,50 m (31,2 ft)	10,20 m (33,5 ft)	10,20 m (33,5 ft)	10,15 m (33,3 ft)
5910 mm (232,7 in)	6050 mm (238,2 in)	6050 mm (238,2 in)	6800 mm (267,7 in)	6800 mm (267,7 in)	6800 mm (267,7 in)
2380 mm (93,7 in)	2420 mm (95,3 in)	2420 mm (95,3 in)	2600 mm (102,4 in)	2700 mm (106,3 in)	2880 mm (113,4 in)
2490 mm (98 in)	2890 mm (113,8 in)	2890 mm (113,8 in)	2930 mm (115,4 in)	2930 mm (115,4 in)	2980 mm (117,3 in)
12100 kg (26676 lb)	16000 kg (35274 lb)	16800 kg (37038 lb)	24500 kg (54013 lb)	27500 kg (60627 lb)	29450 kg (64926 lb)
18x22,5"	17,5x25"	17,5x25"	20,5R25"	23,5R25"	26,5R25"