

DIMENSIONS ARE IN INCHES.  
DIMENSIONS IN [ ] ARE MILLIMETERS.

- 325+ WATTS MINIMUM
- 72-CELL POLYCRYSTALLINE
- 17.5% MAX EFFICIENCY
- 10 YEAR WARRANTY
- MADE IN NORTH AMERICA
- 25 YEAR LINEAR PERFORMANCE
- UL CERTICATION: ULC/ORD-C1703-1, UL1703
- MANUFACTURED ACCORDING TO INTERNATIONAL QUALITY SYSTEM STANDARDS: ISO9001
- GUARANTEED POSITIVE POWER SORTING: [- 0 : +4.99 WP]

### ELECTRICAL DATA (STC)

Peak Rated Power	$P_{mpp}$ (W)	340	335	330	325
MAX Power Voltage	$V_{mpp}$ (V)	38.45	38.05	37.54	37.42
MAX Power Current	$I_{mpp}$ (A)	8.92	8.90	8.85	8.745
Open Circuit Voltage	$V_{oc}$ (V)	48.37	46.28	46.26	46.11
Module Efficiency	Eff (%)	17.5	17.3	17.0	16.7
MAX Series Fuse Rating	MF (A)	15	15	15	15
Short Circuit Current	$I_{sc}$ (A)	9.45	9.20	9.13	9.05

### MECHANICAL DATA

Output Cables	47.2-inch symmetrical cables with MC4 type connectors
Junction Box	IP-67 rated with bypass diodes
Frame	Double webbed 15-micron anodized aluminum alloy
Front Glass	Low-iron content, high transmission PV solar glass
Solar Cells	72 Polycrystalline cells (156 x 156 mm)

## MAXIMUM RATINGS

Operational Temperature	-40F to 185F
System Voltage	1000V

## I – V Curve

