



## Now you can add audio to your casino gaming machines

HyperSound helps casino system owners improve slot machine customer experiences by creating immersive, personalized audio without disturbing employees or other patrons. Uniquely designed for a wide range of gaming applications, HyperSound directed audio speakers can become a key component of your establishment's sales and marketing strategy.

**Sound where you want it, and nowhere else.**

### Create sound zones for multi-sensory gaming environments

Integrating directed audio speakers into tribal gaming systems adds a new level of auditory stimulation, increases customer engagement, and leads to improved casino revenue. HyperSound is uniquely effective for casino environments where sound bleed and background noise is an issue because it beams clear, direct audio messages without being distracting to other players nearby. Directed audio also gives slot machines a competitive edge by improving usability and ease of play, making messages more clear, informative, and memorable.

Lightweight speakers and slim form factor make integration into slot machine design easy.

### Targeted sound zones

allow messages to reach the intended target without disrupting players in the surrounding environment. Create several audio zones without bleed, each playing a different message.


### Clear, engaging audio

makes gaming visuals more attention-grabbing, informative, and memorable – and as a result more effective at eliciting extended or repeated game play.

**WHAT'S INCLUDED:**

		MONO SYSTEM	10-3004-01-00 (BLACK) 10-3004-01-01 (WHITE)	STEREO SYSTEM	10-3003-01-00 (BLACK) 10-3003-01-01 (WHITE)
<b>A</b>	1	HyperSound Speaker		2	HyperSound Speakers
<b>B</b>	1	Set of Red & Black Speaker Cables with Banana Connectors and Audio Cable		2	Sets of Red & Black Speaker Cables with Banana Connectors and Audio Cable
<b>C</b>	1	Amplifier		1	Amplifier
<b>D</b>	1	30 volt DC Power Supply		1	30 volt DC Power Supply

For pricing inquiries,  
please call (619) 670-4412


**PRODUCT SPECIFICATIONS**
**Electrical:**

AC power cord length:  
1.5 meters (5 feet)  
Speaker cord length (14AWG):  
2 meters (6.5 feet)  
Universal power supply:  
Input: 100V-240V-50/60 Hz  
Output: 30V DC @ 1.5 amps

**Mechanical:**

Speaker dimensions:  
12.5 x 6.375 x 2.125 inches  
HSS-3000 amplifier box:  
6.25 x 6.75 x 1.875 inches

**Unit Weight:**

7.4 pounds (3.4 kg)  
(per complete system)

**Colors:**

Black - Standard  
White - Standard

**Environmental:**

Operating temperature:  
10°C to 40°C (50° to 104°F)  
Storage temperature:  
-20°C to 50°C (-4° to 122°F)  
Operating humidity range:  
0 to 95% (non-condensing)  
Storage humidity range:  
0 to 95% (non-condensing)

**System:**

Max audio SPL output:  
(single emitter)  
100dB @ 1.5 kHz/2  
meters

**Audio:**

Impedance:  
10k Ohms  
Input connectors:  
1 RCA style connector  
(per channel)  
Speaker cable connectors:  
2 banana style connectors  
(per emitter)  
Powered subwoofer output:  
1 RCA style  
System configuration:  
Stereo 2 channel or mono  
Max input for max output:  
160 mVrms per channel  
Frequency response:  
300 Hz to 18kHz

**Ultrasonic and DSP Processing:**

Carrier frequency:  
Proprietary in range of 40 kHz  
Modulation method:  
Proprietary and patent  
pending processing

**Ultrasonic Speaker Type:**

HyperSound proprietary, patented and  
patent pending monolithic film  
transducer

**Power Amplification:**

Amplifier type:  
Customized Class D digital  
Amplifier power output: 15 watts

Specifications are subject to change  
without notice.

