

AMERICAN SPECIALTIES, INC.


441 Saw Mill River Road, Yonkers, NY 10701 (914) 476.9000 • (914) 476.0688 www.americanspecialties.com

 MODEL №:
 0371

 ISSUED:
 07-87

REVISED: 12 APR 2019

SURFACE MOUNTED LIQUID SOAP DISPENSER (PUSH-UP TYPE)



SPECIFICATION

Surface Mounted Liquid Soap Dispenser (Push-up type) shall hold and dispense 16 oz (0.5 L) of liquid soap, detergent or lotion having a pH in range 7 ± 1.5 and viscosity in range 150-3500 cP (mPa•s). Soaps containing reportable salts, chlorides and alcohols should be avoided from supply tank. Unit shall be tamper resistant, chrome plated ABS plastic, translucent white polyethylene soap container and a corrosion resistant ABS dispensing valve with stainless steel spring. Valve operation shall comply with 2010 ADA Accessibility Standards and ICC/ANSI A.117.1 by requiring no more than 5 lbs_f (22.2 N) pressure to actuate and require no grasping or twisting by operator.

Surface Mounted Liquid Soap Dispenser shall be Model № 0371 of American Specialties, Inc., 441 Saw Mill River Road, Yonkers, New York 10701-4913

INSTALLATION

Secure unit to wall or partition using three (3) № 10 pan head self-threading screws (supplied). For compliance with 2010 ADA Accessibility Standards install unit so that bottom of unit is 48" [1219] maximum above finished floor (AFF). For general utility install unit 42" [1066] AFF or 6" [152] minimum above counter top.

OPERATION

A measured amount of soap is manually dispensed by pushing-up against valve. Refill unit by unscrewing base from bracket collar, inverting unit and unscrewing soap container. Soap will continue to feed properly until empty. Tank supply is replenished manually on cycle determined by maintenance needs. Soap level is continuously visible.