PORTWEST

PRODUCT SPECIFICATION & TECHNICAL DATA


PS32 - Wrap Around Plus Glasses

Collection: Eye Protection

Range: PPE

Materials: Polycarbonate

Inner Pack: 12 Outer Carton: 300



Best selling wrap around spectacleAvailable with additional edge protection as a result of the removable gasketOffers a super comfortable fit and optimal protection against dust and impactsLenses are treated with antiscratch and anti-fog coating for improved performance

Eve Protection

PORTWEST® eye protection range includes spectacles, safety goggles and vizors, designed to protect the eyes and face of workers from injuries which may occur during working activities. TECHNICAL SPECTACLES: High performance and cutting edge styles. SPORT SPECTACLES: Light weight and modern design. CLASSIC SPECTACLES: Essential PPE safety eyewear styles.

PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

Standards

EN 166 (1FT) EN 170 (2C-1.2) EN 172 (5-3.1 (smoke)) ANSI/ISEA Z87 + (U6)



Features

- · CE Certified
- 99% UV protection
- Anti-scratch coating for added durability
- Anti-fog coating for additional comfort to the wearer
- Detachable foam offers additional protection against shocks and dust
- · Free spec cord
- Flexible arms for ultra comfort
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- New Color

	Range						
	-						
Smoke Lens.							
Smoke Lens, Orange Temple	-						

PORTWEST®

PRODUCT SPECIFICATION & TECHNICAL DATA

PS32 - Wrap Around Plus Glasses Commodity Code: 9004901000

Test House

CERTOTTICA SCARL (Notified Body No.: 0530) Zona Industriale Villanova 32013, Italy

Cert No: 15087

CERTOTTICA SCARL (Notified Body No.: 0530)

Zona Industriale Villanova

32013, Italy

Cert No: AC18089

CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m³)	EAN13	DUN14
PS32CLR	Clear	54.0	51.0	44.0	0.0240	0.1212	5036108273621	15036108763686