


Insulated Lipped Blade Terminals

Material
Insulation: PVC
Terminal Body: Copper
Plating: Tin



Order No.	Dimension (mm)					Colour
	B	L	F	H	D	
318-150	4.6	26.8	16.8	10.0	4.3	Red
318-250	4.6	26.8	16.8	10.0	4.9	Blue
318-600	4.6	29.8	16.8	13.0	6.7	Yellow




Screw-on Wire Connector

Material
Insulation: PVC
Terminal Body: Steel
Plating: Zinc



Order No.	Dimension (mm)			Wire Range (mm ²)	Colour
	A	B	C		
319-000	7.4	9.8	17.6	Min 0.75 x 3 ; Max 1.5 x 3	Blue
319-001	11.2	14.0	24.6	Min 0.25 x 1 + 0.75 x 1 ; Max 2.5 x 4 + 0.75 x 1	Yellow
319-002	13.3	16.4	26.5	Min 0.25 x 2 ; Max 6 x 2 + 4 x 2	Red



Copper Connecting Tube

Material
Terminal Body: Copper
Plating: Tin



Order No.	Dimension (mm)			Wire Range (mm ²)
	d	D	L	
322-001	3.5	2.5	20	1.5
322-002	4.0	3.0	20	2.5
322-004	4.8	3.5	20	4
322-006	5.5	4.1	25	6
322-010	6.7	5.0	30	10
322-016	7.5	5.8	35	16
322-025	9.0	7.2	40	25
322-035	10.5	8.5	45	35
322-050	12.5	10.1	50	50
322-070	14.5	11.7	55	70
322-095	17.0	13.8	60	95
322-120	19.5	15.9	65	120
322-150	20.5	16.7	70	150
322-185	23.5	19.1	75	185
322-240	26.0	21.4	80	240
322-300	30.0	24.6	85	300
322-400	34.0	27.4	90	400
322-500	38.0	30.8	100	500
322-630	45.0	35.8	110	630

