

Splicing End Quick Connectors

Material
Material ; PVC
Conductor Material ; Copper
Actuation Type ; Lever



Order No.	Number of Connections	Cable Range min (mm2)	Cable Range max (mm2)	Rated Voltage	Rated Current	Qty/Pkt
323-002	2	0.08	4	400V	32A	100
323-003	3	0.08	4	400V	32A	50
323-004	4	0.08	4	400V	32A	50
323-005	5	0.08	4	400V	32A	50
323-008	8	0.08	4	400V	32A	50

Splicing In-line Quick Connectors

Material
Material ; PVC
Conductor Material ; Copper
Actuation Type ; Lever



Order No.	Number of Connections	Cable Range min (mm2)	Cable Range max (mm2)	Rated Voltage	Rated Current	Qty/Pkt
324-002	2	0.08	4	400V	32A	50
324-003	3	0.08	4	400V	32A	30

Push Wire Quick Connectors

Material
Material ; PVC
Conductor Material ; Copper
Actuation Type ; Push



Order No.	Number of Connections	Cable Range min (mm2)	Cable Range max (mm2)	Rated Voltage	Rated Current	Qty/Pkt
325-002	2	0.75	2.5	400V	32A	100
325-004	4	0.75	2.5	400V	32A	100
325-006	6	0.75	2.5	400V	32A	100

Compact Splicing Quick Connectors

Material
Material ; PVC
Conductor Material ; Copper
Actuation Type ; Lever



Order No.	Number of Connections	Cable Range min (mm2)	Cable Range max (mm2)	Rated Voltage	Rated Current	Qty/Pkt
326-002	2	0.5	2.5	450V	32A	100
326-003	3	0.5	2.5	450V	32A	100
326-004	4	0.5	2.5	450V	32A	100
326-005	5	0.5	2.5	450V	32A	50
326-006	6	0.5	2.5	450V	32A	50
326-008	8	0.5	2.5	450V	32A	50