



Qinyang Xianfeng Insulation Material Plant  
 Tel: +86-18339769018 Email: [meng@hnxianfeng.cn](mailto:meng@hnxianfeng.cn)  
 Add: Dongxiang Industrial Park, Qinyang City, Henan Province, China

## 2715 PVC Glass fiber sleeving

2715 Fiberglass PVC sleeving is fiberglass sleeving coated with PVC resin, with very good flexibility and dielectric features. Fiberglass PVC sleeving consists of a fiberglass braid with an electrical grade PVC coating specially formulated for exceptional heat resistance and stability. It is widely used as insulating and protection material for motor and electric appliance.

### Type Specifications

Size	VICATA	voltage level	average voltage	minimum
Pvc sleeve	+ 200°C -30°C	A	4000V	4000V

### Inside Diameter: (mm)

Size	Inside Diameter (mm)	Min Wall thickness
		7000V
Φ 0.5	0.5+0.20/-0	0.38
Φ 1.0	1.0+0.20/-0	0.38
Φ 1.5	1.5+0.20/-0	0.38
Φ 2.0	2.0+0.20/-0	0.38
Φ 2.5	2.5+0.20/-0	0.38
Φ 3.0	3.0+0.25/-0	0.46
Φ 3.5	3.5+0.23/-0	0.46
Φ 4.0	4.0+0.25/-0	0.46
Φ 4.5	4.5+0.25/-0	0.46
Φ 5.0	5.0+0.35/-0	0.50
Φ 6.0	6.0+0.35/-0	0.50
Φ 7.0	7.0+0.50/-0	0.54
Φ 8.0	8.0+0.50/-0	0.54
Φ 9.0	9.0+0.50/-0	0.54
Φ 10.0	10+0.70/-0	0.64
Φ 12.0	12+0.70/-0	0.64

