

## Flexible metallic conduit systems

### Type GAM & GBM - KE Ultra fittings

#### Type GAM – Fixed body, straight fitting - Fixed external male thread for covered conduit

Materials: Nickel plated zinc or Nickel plated brass



Part no.	Metric thread size	Ext. thread outside diameter (mm)
GAM0303*	M16	16.0
GAM0304*	M20	20.0
GAM0404**	M20	20.0
GAM0505**	M25	25.0
GAM0606**	M32	32.0
GAM0707*	M40	40.0
GAM0808*	M50	50.0
GAM0909*	M63	63.0
GAM1010*	M75	75.0

\*Nickel plated brass body &amp; Ferrule.

\*\*Nickel plated cast zinc body with nickel plated brass ferrule.

#### Approvals



#### Approvals

BSI Kitemark / KM-35161  
CE Mark to the low voltage directive

#### IP Rating

**IP54** Waterproof with KEBF and KEBT

#### Temperature range

Static temperature: -65°C to +350°C  
Dynamic temperature: -45°C to +250°C

#### Degree of mechanical protection

Very high

#### Type GBM – Swivel body, straight fitting - Swivel external male thread for covered conduit

Materials: Nickel plated brass



Part no.	Metric thread size	Ext. thread outside diameter (mm)
GBM0303	M16	16.0
GBM0404	M20	20.0
GBM0505	M25	25.0
GBM0606	M32	32.0
GBM0707	M40	40.0
GBM0808	M50	50.0

#### Approvals



#### Approvals

BSI Kitemark / KM-35161  
CE Mark to the low voltage directive

#### IP Rating

**IP54** Waterproof with KEBF and KEBT

#### Temperature range

Static temperature: -65°C to +350°C  
Dynamic temperature: -45°C to +250°C

#### Degree of mechanical protection

Very high