

**Stainless Steel Ball Lock Cable Ties, Coated**

**Technical Information:**

**Material** A) 316 grade non-magnetic stainless steel  
B) 304 grade non-magnetic stainless steel

**Temperature Range** - 80°C to +150°C

**Surface Finish** Pure Polyester & Epoxy Coating

**Flamability rating** Fireproof, Halogen Free and UV-resistant



**Ball Lock Coated-SS304, 4.6mm width**

Part No.	Material	Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
		In	mm	In	mm	In	mm	In	mm	N	lbs	
BC44-100	SS304	0.18	4.6	4	100	0.01	0.25	1.1	27	667	150	100/bag
BC44-150	SS304	0.18	4.6	6	150	0.01	0.25	1.7	43	667	150	100/bag
BC44-200	SS304	0.18	4.6	8	200	0.01	0.25	2.3	59	667	150	100/bag
BC44-260	SS304	0.18	4.6	10	260	0.01	0.25	3.1	78	667	150	100/bag
BC44-360	SS304	0.18	4.6	14	360	0.01	0.25	4.3	110	667	150	100/bag
BC44-520	SS304	0.18	4.6	20	520	0.01	0.25	6.3	161	667	150	100/bag
BC44-620	SS304	0.18	4.6	24	620	0.01	0.25	7.6	192	667	150	100/bag
BC44-840	SS304	0.18	4.6	33	840	0.01	0.25	10.4	263	667	150	100/bag
BC44-1000	SS304	0.18	4.6	39	1000	0.01	0.25	12.3	313	667	150	100/bag

**Ball Lock Coated-SS316, 4.6mm width**

Part No.	Material	Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
		In	mm	In	mm	In	mm	In	mm	N	lbs	
BC46-100	SS316	0.18	4.6	4	100	0.01	0.25	1.1	27	667	150	100/bag
BC46-150	SS316	0.18	4.6	6	150	0.01	0.25	1.7	43	667	150	100/bag
BC46-200	SS316	0.18	4.6	8	200	0.01	0.25	2.3	59	667	150	100/bag
BC46-260	SS316	0.18	4.6	10	260	0.01	0.25	3.1	78	667	150	100/bag
BC46-360	SS316	0.18	4.6	14	360	0.01	0.25	4.3	110	667	150	100/bag
BC46-520	SS316	0.18	4.6	20	520	0.01	0.25	6.3	161	667	150	100/bag
BC46-620	SS316	0.18	4.6	24	620	0.01	0.25	7.6	192	667	150	100/bag
BC46-840	SS316	0.18	4.6	33	840	0.01	0.25	10.4	263	667	150	100/bag
BC46-1000	SS316	0.18	4.6	39	1000	0.01	0.25	12.3	313	667	150	100/bag

**Ball Lock Coated-SS304, 7.9mm width**

Part No.	Material	Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
		In	mm	In	mm	In	mm	In	mm	N	lbs	
BC74-100	SS304	0.31	7.9	4	100	0.01	0.25	1.1	27	1335	300	100/bag
BC74-150	SS304	0.31	7.9	6	150	0.01	0.25	1.7	43	1335	300	100/bag
BC74-200	SS304	0.31	7.9	8	200	0.01	0.25	2.3	59	1335	300	100/bag
BC74-260	SS304	0.31	7.9	10	260	0.01	0.25	3.1	78	1335	300	100/bag
BC74-360	SS304	0.31	7.9	14	360	0.01	0.25	4.3	110	1335	300	100/bag
BC74-520	SS304	0.31	7.9	20	520	0.01	0.25	6.3	161	1335	300	100/bag
BC74-620	SS304	0.31	7.9	24	620	0.01	0.25	7.6	192	1335	300	100/bag
BC74-840	SS304	0.31	7.9	33	840	0.01	0.25	10.4	263	1335	300	100/bag
BC74-1000	SS304	0.31	7.9	39	1000	0.01	0.25	12.3	313	1335	300	100/bag

**Ball Lock Coated-SS316, 7.9mm width**

Part No.	Material	Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
		In	mm	In	mm	In	mm	In	mm	N	lbs	
BC76-100	SS316	0.31	7.9	4	100	0.01	0.25	1.1	27	1335	300	100/bag
BC76-150	SS316	0.31	7.9	6	150	0.01	0.25	1.7	43	1335	300	100/bag
BC76-200	SS316	0.31	7.9	8	200	0.01	0.25	2.3	59	1335	300	100/bag
BC76-260	SS316	0.31	7.9	10	260	0.01	0.25	3.1	78	1335	300	100/bag
BC76-360	SS316	0.31	7.9	14	360	0.01	0.25	4.3	110	1335	300	100/bag
BC76-520	SS316	0.31	7.9	20	520	0.01	0.25	6.3	161	1335	300	100/bag
BC76-620	SS316	0.31	7.9	24	620	0.01	0.25	7.6	192	1335	300	100/bag
BC76-840	SS316	0.31	7.9	33	840	0.01	0.25	10.4	263	1335	300	100/bag
BC76-1000	SS316	0.31	7.9	39	1000	0.01	0.25	12.3	313	1335	300	100/bag

