



PRODUCT SELECTION INFORMATION: DIMENSIONS IN INCHES (mm)						
Description	Primary Insulation Conductor Size (AWG/Kcmil)	1000V Use Range	General Use Range	Length	Wall Thickness (min. - max.)	Standard Pack (pcs./Box)
CRSM 34/10-200	#8 - 2/0	0.25 - 0.60 (6 - 15)	0.25 - 1.20 (6 - 30)	8 (200)	0.02 - 0.1 (0.3 - 2.4)	3
CRSM 34/10-1200	#8 - 2/0	0.25 - 0.60 (6 - 15)	0.25 - 1.20 (6 - 30)	48 (1219)	0.02 - 0.1 (0.3 - 2.4)	5
CRSM 53/13-200	3/0 - 400	0.60 - 0.95 (15 - 24)	0.60 - 1.80 (15 - 46)	8 (200)	0.02 - 0.08 (0.3 - 2)	10
CRSM 53/13-1200	3/0 - 400	0.60 - 0.95 (15 - 24)	0.60 - 1.80 (15 - 46)	48 (1219)	0.02 - 0.08 (0.3 - 2)	5
CRSM 84/20-750	500 - 1000	0.95 - 1.40 (24 - 36)	0.95 - 2.70 (24 - 69)	30 (750)	0.02 - 0.08 (0.3 - 2)	10
CRSM 84/20-1200	500 - 1000	0.95 - 1.40 (24 - 36)	0.95 - 2.70 (24 - 69)	48 (1219)	0.02 - 0.08 (0.3 - 2)	5
CRSM 107/29-1000	1000 - 2000	1.30 - 2.00 (33 - 51)	1.30 - 3.60 (33 - 91)	40 (1000)	0.02 - 0.08 (0.3 - 2)	10
CRSM 107/29-1200	1000 - 2000	1.30 - 2.00 (33 - 51)	1.30 - 3.60 (33 - 91)	48 (1219)	0.02 - 0.08 (0.3 - 2)	5
CRSM 143/36-1200	-	-	1.65 - 4.95 (42 - 126)	48 (1219)	0.02 - 0.08 (0.3 - 2)	5
CRSM 198/55-1200	-	-	1.65 - 4.95 (42 - 126)	48 (1219)	0.02 - 0.09 (0.3 - 2.1)	5

Dimension values provided are typical. Related test reports: EDR-5124, 5192, 5361.

REFERENCE DIMENSIONS FOR FIELD CUTTING OF CRSM: INCHES (mm)	
Damage Length	Total Seal Length
<3 (<76)	3 (76)
3 - 12 (76 - 305)	4 (102)
12 - 24 (305 - 610)	6 (152)
> 24 (>610)	8 (203)

Cut Sleeve Length = Damage Length + Total Seal Length

ORDERING INFORMATION

Kit includes wraparound sleeve and stainless steel channel closure. Both can be field cut for shorter requirements. Kit does not include connectors

Bulk options are also available. Consult your TE Connectivity representative.

te.com/energy

© 2014 TE Connectivity Ltd. family of companies. All Rights Reserved. E561 10/2014

CRSM, Raychem, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

- USA: + 1 800 327 6996
- France: + 33 380 583 200
- UK: + 44 0870 870 7500
- Germany: + 49 896 089 903
- Spain: + 34 916 630 400
- Benelux: + 32 16 351 731
- Canada: + 1 (905) 475-6222
- Mexico: + 52 (0) 55-1106-0800
- Latin/S. America: + 54 (0) 11-4733-2200
- China: + 86 (0) 400-820-6015