


Insulated Male Disconnects


Material
Insulation: PVC
Terminal Body: Brass
Plating: Tin



Order No.	Nema Tab (mm)	Dimension					Colour
		B	d	D	L	H	
307-150	0.8 x 6.35	6.35	1.7	4.3	21.0	10.0	Red
307-250	0.8 x 6.35	6.35	2.3	4.3	21.0	10.0	Blue
307-600	0.8 x 6.35	6.35	3.4	5.7	25.0	13.0	Yellow

Insulated Female Disconnects


Material
Insulation: PVC
Terminal Body: Brass
Plating: Tin



Order No.	Nema Tab (mm)	Dimension					Colour
		B	d	D	L	H	
308-150	0.8 x 6.35	7.4	1.7	3.8	21.0	10.0	Red
308-250	0.8 x 6.35	7.4	2.3	4.3	21.0	10.0	Blue
308-600	0.8 x 6.35	7.4	3.4	5.7	29.6	13.0	Yellow

Insulated Butt Connectors

Material
Insulation: PVC
Terminal Body: Copper
Plating: Tin



Order No.	Dimension (mm)			Wire Range		Imax	Colour
	l	d	L	A.W.G	mm ²		
310-150	15.0	1.7	26.0	22-16	0.5-1.5	19A	Red
310-250	15.0	2.3	26.0	16-14	1.5-2.5	27A	Blue
310-600	15.0	3.4	26.0	12-10	4-6	48A	Yellow