


Brass NP Cable Glands


Material
 IP Rating :IP68
 Material : Brass Plated with Nickel
 Weather Strip: Nitrile Butadiene Rubber (NBR)
 weathering resitant rubber EPDM



Order No.	Thread Size	Cable Range (mm)	Thread O.D L2 (mm)	Thread Length L1 (mm)	Spanner Size (mm)	Qty/Bag
355-012	M12 x 1.5	3-6	10	8	15	100
355-016	M16 x 1.5	4-8	16	9	22	100
355-020	M20 x 1.5	6-11	20	10	27	100
355-025	M25 x 1.5	12-15	25	11	31	100
355-032	M32 x 1.5	16-21	32	12	38	50
355-040	M40 x 1.5	22-32	40	15	52	50
355-050	M50 x 1.5	32-38	50	18	62	25
357-007	PG7	3-6.5	12.5	9	18	100
357-009	PG9	4-8	15.2	9	22	100
357-011	PG11	5-10	18.6	9	24	100
357-013	PG13.5	6-11	20.4	10	27	100
357-016	PG16	10-13	22.5	10	30	100
357-019	PG19	12-15	24	10	30	100
357-021	PG21	13-18	28.3	12	35	100
357-029	PG25	16-21	30	12	37	100
357-036	PG29	18-25	37	12	45	50

Terminal Blocks

Material
 Nylon PA66
 Volatge: 400V



Order No.	Dimension (mm)					wire range mm2	Amp	Qty/Bag
	L	W	H	A	B			
390-006	115.0	15.7	13.0	6.5	9.5	6	6	10
390-010	126.0	20.2	15.5	8.4	10.5	10	10	10
390-016	139.0	23.0	17.7	10.3	12.0	12	16	10
390-020	155.0	25.0	19.2	11.5	13.5	14	20	10
390-030	171.0	26.0	20.5	12.0	14.5	16	30	10

