





### TRIUMPH STREET TRIPLE

#### FENDER ELIMINATOR (2013-2017)

- 1 Underneath seat, unplug stock connector (picture 1)
- 2 With an 8mm socket, remove (4) bolts (picture 2)
- 3 Remove stock fender
- 4 Disassemble stock fender to expose wiring and unplug connectors for turn signals and plate light (picture 3)
- 5 Remove (4) bolts with 8mm socket and 4mm allen key or socket to remove plastic panel (picture 4)
- 6 To remove tail light, unbolt (2) 8mm bolts and unplug connector (picture 5)
- 7 On tail light, remove (2) 4mm bolts (picture 6)
- 8 Slide new tail light into plastic cavity, and install 4mm bolts (picture 7)



# NEW RAGE CYCLES

## INSTALLATION INSTRUCTIONS

### FENDER ELIMINATOR (2013-2017)

- 9 Remove 4mm allen bolt to loosen plastic panel so module will fit (picture 8)
- 10 Reinstall (3) tail light bolts with 8mm socket and 4mm allen (picture 9)
- 11 Reinstall (4) bolts for plastic panel over top of brake light with 8mm socket and 4mm allen (picture 10)
- 12 Wire in module using supplied wiring diagram. Shrink tube connections when complete.
- 13 With supplied M6x10 and tooth washers, bolt license plate to diamond plate (picture 11)
- 14 With 1/2" white spacers, use M5 bolts and nuts to bolt on diamond plate (picture 12)
- 15 Reuse the 2 factory spacers and slide them onto the 2 holes for the supplied M5 bolts to go through (picture 13)
- 16 Mount license plate
- 17 Put seat back on

