



Unified Collaboration System

Genee X Series Range

The Genee X Series is the revolutionary addition to a business environment; it comes inclusive with Windows 365 and Skype for Business, ensuring the limitless possibilities of interacting with staff and clients anywhere around the world. It has been designed to achieve effective meetings, to enhance your presentation experience further and to create a visual impact on your audience. With its crystal clear and precise InGlass technology and its Intelligent Touch feature, your screen presentations can be conducted with ease. Whether you are using your fingers or a pen to write, annotating and producing interactive presentations has never felt so accurate, smooth and natural, giving you the extra confidence when presenting in front of an audience. The X Series has been designed specifically with an optically bonded 4K display to ensure the high definition of clarity, the screen provides a 178° viewing angle and this ensures that all individuals can still see the image on the screen very clearly no matter where they are sitting.

The X Series allows for a full Bring Your Own Device (B.Y.O.D) experience. Simply connect through your laptop, smartphone or tablet to achieve a seamless team collaboration. Utilising Genee software such as Project Flow and CubeShare allows further collaborative opportunities, enabling presentations to be shared amongst your staff and clients. Genee Spark II software is the perfect tool for collective ideas, solutions and strategies to be brainstormed, a place that allows employees to channel their creativity and focus. We want to ensure that you get the maximum experience of your G-Touch screen, which is why Spark II comes available with every screen for free and not only that, but you also get a 90 day trial of Project Flow.

For the ultimate solution, pair up your X Series with the Genee OPS, this will enable you to upgrade your touchscreen to your individual business requirements and the OPS unit can also be interchangeable with other devices. The X Series comes available in the sizes: 65", 70", 75" & 86"

Key Features & Benefits



Spark II Software

The ultimate presentation software, uniquely designed for 4K screens and is free with our Genee screens.



Project Flow Software

Encourages collaboration and enables the presenter to gain live instant feedback during a presentation. 90 day free trial.



Enhanced Acoustics

Acoustic echo cancellation and noise reduction technology enables meeting participants to be heard clearly across a 8-metre room.



Interchangeable Video Cameras

Two interchangeable front-facing cameras, positioned at the top and bottom of the screen, providing crisp video conferencing.



High Quality Sound

Two high quality front facing speakers, allowing the whole room to hear a presentation or video clearly.



InGlass Technology

Utilising the latest InGlass technology, the X Series allows presenters to annotate with ease and produce interactive presentations.

Discover more about our range of visualisers, interactive touchscreens, audience response systems and software.

READY TO SERVE YOU!
01902 422 300

Genee X Series Range

product specification

	X6	X8	X9
Product Code	TOU060010	TOU060020	TOU060030
Size & Type	65" LED 4K, Resolution: 3840 x 2160, (16:9)	75" LED 4K, Resolution: 3840 x 2160, (16:9)	86" LED 4K, Resolution: 3840 x 2160, (16:9)
Display Colours	8-bit	8-bit	10-bit
Brightness	≥320nit	≥320nit	370nit
Contrast	4000:1		
Response Time	8ms		
SPEAKER			
Speaker Position	Forward (2 x15W Max Power Output)		
Output S.P.L.	≤13W		
MICROPHONE			
Polar Patterns	Omni-directional		
Pickup Range	8m		
CAMERA			
Position	Top x 1, Bottom x 1		
Lens	86°		
Video Resolution	1920 x 1080 @30fps (Max), Frame Rate: 30fps/60fps		
ELECTRICAL			
Power Consumption	Maximum ≤220W Standby Mode ≤0.5W	Maximum ≤300W Standby Mode ≤0.5W	Maximum ≤450W Standby Mode ≤0.5W
Working Voltage	AC 100-240V, 50/60Hz		
TOUCH			
Touch Sensor	InGlass, 20 Point Touch		
TRANSPORTATION / STORAGE			
Mounting (optional)	Wall-mounted/Floor Stand		
Dimensions (W x H x D)	1568 X 1045 X 88MM	1792 X 1170 X 102MM	2039 X 1315 X 101MM
Net Weight	45 kg	55 KG	71.6 KG
PORTS			
Front Interface Inputs	HDMI 1.4 (4K@30Hz) x1, USB(Touch) x1, USB (Dynamic) x2, Microphone In x1		
AV Inputs	HDMI (4K@60Hz x2, 4K@30Hz x1), DP (4K@60Hz) x1, USB (Touch) x4		
AV Outputs	HDMI Out (4K@60Hz) x1, Line Out x1, SPDIF out		
Other	USB2.0 x2 (Dynamic), RS232 x1, RJ45 x2 (In, Out), USB3.0 x1, OPS Slots (4K@60Hz), DC 5V-2A out		
SYSTEM			
Build in Wi-Fi	2.4G/5G		
Software	Project Flow; 90 Day Free Trial. Spark II lifetime license. Genee App Store (downloadable)		
OPS PC	Intel Core i7-6500U, 2*4GB DDR4, 256GB SSD, 4K@60HZ, TPM2.0		