



## IB928

Access Control

### Active Cotag clamshell card

---

- Includes lithium battery
- Factory encoded

The IB928 is a factory-encoded active card that includes a lithium battery which enables it to provide hands-free functionality when it is used together with Cotag hands-free readers. For example, the combination of the IB928 card and the HF500-Cotag reader results in a reading range of approximately 102 cm. The reading range when the IB928 is used in combination with Cotag proximity readers varies from approximately 12 to 32 cm. IB928 cards are particularly useful in environments where some cardholders are disabled or often have their hands full (i.e. a hospital or warehouse).

One of the major advantages of Cotag technology is that active and passive cards can be mixed in the same system to provide ultimate convenience and cost-efficiency.

Note: The card number is printed on the back of the card.

Quantity in order: 1

## Technical data

---

### IB928

---

Dimensions (W x H x D) 53.89 x 85.85 x 2.89 mm

---

## Card read distance

---

Reader	HF500-Cotag	BC5511-Cotag	BC5516-Cotag	HD500-Cotag	PR500-Cotag	PP500-Cotag	SP500-Cotag	PM500-Cotag
IB928	Up to 109 cm	Up to 112 cm	Up to 300 cm	Up to 26 cm	Up to 32 cm	Up to 12 cm	Up to 29 cm	Up to 23 cm

## Details for ordering

---

Type	Part no	Designation
IB928	S24246-D5203-A1	Active Cotag clamshell card

Issued by  
Siemens Building Technologies  
Fire & Security Products GmbH & Co. oHG  
D-76181 Karlsruhe  
www.buildingtechnologies.siemens.com

© 2009 Copyright by  
Siemens Building Technologies  
Fire & Security Products GmbH & Co. oHG  
Data and design subject to change without notice.  
Supply subject to availability.