



3 years **warranty**



Biometrics



RFID



Barcode



QR Code

## Qualica-RD **CANOPUS 60**

The tripod that adapts to small installation spaces.

**Qualica-RD CANOPUS 60**, silent and compact bi-directional tripod. The upper part is covered with high quality black tempered glass. Guarantees an average of 15 million steps without impact on the brushless mechanics.

With emergency opening, automatic reset function, LED indicators, alarm and anti-intrusion function. Integrated lights on the doors to mark valid or invalid access. Color, logo and dimensions can be customized.

**3 years warranty.** Ideal for hotels, gyms, buildings, shopping malls, supermarkets, reception areas, etc.



# CANOPUS 60 Tripod

## Features

- It is ideal for both indoor and outdoor use IP65.
- In case of emergency, the tripod arms lower automatically to allow free passage.
- The whole system operates with low noise and no mechanical impact.
- Automatic reset function: the turnstile arm will automatically lock within 5 seconds.
- It has standard relay signal, which can integrate with any kind of third party access control system.



## Technical specifications

<b>Certifications</b>	Compliance CE, ROHS, FCC
<b>Comunication</b>	Dry contact, Relay signal, RS485
<b>Framework Material</b>	304 Brushed Stainless Steel / High end black tempered film glass
<b>Arm Material</b>	304 Stainless Steel
<b>Dimensions</b>	332 * 324 * 1000mm
<b>Net Weight</b>	40kg/pcs
<b>Passage Width</b>	550mm
<b>Passing Direction</b>	Single directional and Bi-directional
<b>MCBF</b>	15 million
<b>Power Supply</b>	AC220V/110V, 50/60Hz
<b>Operation Voltage</b>	24V DC
<b>Power Consumption</b>	40W
<b>Operation Temperature</b>	-20 °C - 75 °C
<b>Operation Humidity</b>	0 ~ 95% (no freeze)
<b>Working Environment</b>	Indoor / Outdoor
<b>Flow rate</b>	35 people per minute
<b>LED Indicator</b>	Two LED indicators on top, front and black
<b>Emergency</b>	Arms will drop down automatically
<b>Flexibility</b>	Integrate with any access control



## Dimensions (mm)

