

CDVI Readers

Proximity, keypad, combined

Wiegand

NANO

Mini proximity reader



- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- NANOPB - black
- NANOPW - white
- 70 x 43 x 23mm

MOONAR

Flush proximity reader



- Multicolour LED
- Audible feedback
- Fits UK back box
- Operating temp. -30°C to 60°C
- Power 12Vdc
- MOONARPB - black
- MOONARPW - white
- 92 x 85 x 13mm

STAR

Mullion proximity reader



- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- STARPB - black
- STARPW - white
- 130 x 41 x 28mm

DGLIWLC & DGLIFWLC

Stainless steel proximity readers

DGLIFWLC



DGLIWLC



- Stainless steel proximity reader
- Vandal resistant housing
- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- 140 x 35 x 22mm DGLIFWLC
- 97 x 76 x 20mm DGLIWLC

SOLAR

Standard proximity reader



- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- SOLARPB - black
- SOLARPW - white
- 130 x 90 x 35mm

KCPROXWLC

Proximity card reader and keypad



- Vandal resistant housing
- Backlit keys
- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- 190 x 43 x 27mm

SOLARK

Proximity card reader and keypad



- Touch sensitive keypad
- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- SOLARKPB - black
- SOLARKPW - white
- 130 x 90 x 35mm

GALEO/W

26-bit Wiegand keypad



- Heavy-duty ZAMAK cast alloy
- Soft blue back-lighting
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- 110 x 75 x 15mm