

# X Series™

## Technical Specifications:



### Xtremely Small, Light, and Powerful

- At less than 12 pounds/6 kilograms, the X Series is about half the size and weight of other full-featured devices.
- Its large, bright screen allows for simultaneous viewing of four traces, all 12 ECG leads, or static and dynamic 12-lead views on a “split screen.”
- The device also incorporates the latest, most advanced and most complete monitoring capabilities, including “gold standard” Masimo® rainbow® SET Pulse CO-Oximetry and Welch Allyn’s Rapid NIBP technology to improve accuracy and reliability.

### CPR with Confidence

- CPR Dashboard™ provides real-time numeric depth and rate values and has a CPR timer that switches to an idle timer when compressions are stopped. The release indicator and the perfusion performance indicator (PPI) also help maximize CPR performance.
- See-Thru CPR® (unique to ZOLL®) helps minimize the duration of interruptions by filtering out artifact, allowing you to see organized underlying rhythms during CPR.

### Unsurpassed 12-lead Data Collection and Communications Capabilities

- The X Series is the first monitor/defibrillator with integrated WiFi. Bluetooth® and USB cellular modem capabilities are standard as well.
- In conjunction with the new RescueNet® Link EMS communications system, patient data can be automatically uploaded and streamed\* to remote displays in ambulances, hospitals, and communication centers while the rescuer cares for the patient on scene and in transit.
- The X Series acquires, stores, and transmits 12-leads to ZOLL's easy-to-use and economical RescueNet 12-Lead and RescueNet MedGate 12-Lead management systems.

## General

**Weight:** 11.7 lbs. (5.3 kg) with battery and paper  
**Dimensions:** 8.9 in (22.6 cm) x 10.4 in (26.4 cm) x 7.9 in (20.1 cm)  
**Enclosure Protection:** Solid Foreign Object: IEC 60529, IP5X  
**Water:** IEC 60529, IPX5  
**Operating Temperature:** 0 to 50°C  
**Humidity:** 15 to 95% RH (non-condensing)  
**Vibration:** MIL-STD 810G, Method 514.6, 4.4.2 Procedure II  
EN ISO 9919 (per IEC 60068-2.64)  
EN 1789 for ambulance. RTCA/DO-160G (multiple helicopter frequencies)  
**Shock:** IEC 60068-2-27, 100g, 6 ms half sine  
**Drop:** EN 1789, 30-inch functional drop, IEC 60601-1, tested at 2 meters  
**Altitude:** -170 m to 4572 m (-557 feet to 15,000 feet)

## Monitor/Display

**Size:** 6.5 in (16.56 cm) diagonal  
**Input:** 3-lead, 5-lead, or 12-lead patient cable, paddles, or multifunction electrodes  
**Type:** Color LCD, 640 x 480 pixels, 800 MCD  
**Sweep Speed:** 25 mm/sec or 50 mm/sec (user selectable)  
**Lead Selections:** Paddles (Pads), I, II, III, AVR, AVL, AVF, V1-6  
**Frequency Response:** (user selectable)  
0.67 – 20 Hz Limited mode  
0.67 – 40 Hz Monitor mode  
0.25 – 40 Hz Filtered diagnostic mode  
0.05 – 150 Hz Diagnostic mode

## Defibrillator

**Waveform:** Rectilinear Biphasic™  
**Energy Selections:** 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 15, 20, 30, 50, 70, 85, 100, 120, 150, 200 joules  
**Energy Display:** Display indicates selected and delivered energy  
**Charge Time:** Less than 7 seconds with a new, fully charged battery  
**Charge Controls:** Front panel and on apex paddle  
**Pads/Paddles:** Hands-free pads and external adult and pediatric paddles. Adult paddles slide off to expose pediatric paddles.  
**Synchronized Mode:** Synchronizes defibrillator pulse to patient's R wave. "SYNC" message displayed on monitor and markers shown on both monitor and recorded ECG. Meets Clause 104 of AAMI DF80.

## Patient Modes

**User Selectable:** Adult, Pediatric, Neonate. Automatically sets configurable defaults for alarm limits, defibrillation energy, and NIBP settings.

## Trends (on-screen)

Tabular numeric format  
All parameters trended/viewable  
**Trend Intervals:** 1, 5, 10, 15, 30, 60 minutes  
**Duration:** 24 hours at 1-minute intervals  
**Snapshots:** Minimum of 32 (12 seconds of pre- and post-button press)  
Quick-access trend display via quick-access button

## Memory Capacity

A combination of 24 hours of trends at 1-minute intervals, 1000 time-stamped events, and 32 snapshots, including monitor, defibrillator, pacer, and treatment snapshots

## Pacer

**Type:** External transcutaneous pacing  
**Pulse Types:** Rectilinear, constant current  
**Pulse Width:** 40 ms ± 2 ms  
**Pacer Rate:** 30 – 180 bpm ± 1.5%  
**Output Current:** 0 – 140 mA ± 5% or 5 mA, whichever is greater  
**Modes:** Demand and Fixed

## CPR

### CPR Feedback Technology

See-Thru CPR®: Artifact filtering  
Real CPR Help®: Real-time depth and rate feedback  
CPR Dashboard™: Numeric readout of depth and rate, release indicator, perfusion performance indicator (PPI)

## ECG

**Cable Detection:** Automatic 3-, 5-, 12-lead ECG  
**Input:** 3-lead cable, 5-lead cable, 12-lead cable, paddles, therapy cable  
**Leads:** I, II, III, AVR, AVL, AVF, V1 – V6  
**Heart Rate Range:** 30 – 300 bpm  
**Heart Rate Accuracy:** ± 3 bpm or 3%  
**Pacer Detection and Display**  
**ECG Sizes:** 0.125, 0.25, 0.5, 1, 2, 4 cm/mV, and auto-ranging  
**Sweep Speed:** 25 mm/sec, 50 mm/sec

## Masimo® SET SpO<sub>2</sub>

**Saturation Range:** 1 – 100%  
**Saturation Accuracy:**  
Oxygen saturation during no-motion conditions:  
Adults, Pediatrics: 70 – 100%, ± 2 digits  
0 – 69%, unspecified  
Neonates: 70 – 100%, ± 3 digits  
0 – 69%, unspecified  
Oxygen saturation during motion conditions  
Adults, Pediatrics: 70 – 100%, ± 3 digits  
0 – 69%, unspecified  
Neonates: 70 – 100%, ± 3 digits  
0 – 69%, unspecified  
Oxygen saturation during low-perfusion conditions:  
Adults, Pediatrics 70 – 100%, ± 2 digits  
0 – 69%, unspecified  
Neonates, 70 – 100%, ± 3 digits  
0 – 69%, unspecified

## Pulse Rate Range:

25 – 240 bpm  
Pulse rate during no-motion conditions:  
Adults, Pediatrics,  
Neonates: 25 – 240 ± 3 digits  
Pulse rate during motion conditions  
Adults, Pediatrics,  
Neonates: 25 – 240 ± 5 digits  
**SpO<sub>2</sub> Average time setting:**  
4, 8 (default), 16 seconds

## Masimo rainbow® SET SpCO®

Range: 0 – 99%  
Accuracy: 1 – 40% ± 3 digits

## Masimo rainbow® SET SpMet®

Range: 0 – 99%  
Accuracy: 1 – 15% ± 1 digits

## Non-Invasive Blood Pressure (NIBP)

Smartcuf® and Sure BP® NIBP technology  
**Measurement Intervals:** Automatic 1-, 2-, 3-, 5-, 10-, 15-, 30-, 60-minute, and manual quick-action NIBP Start/Stop button  
**TurboCuf:** 5 min of repeated NIBP readings  
**Display:** Systolic, diastolic, mean. Viewable on-screen with large numerics.

## Cuff Overpressure Protection

**Typical Measurement Time:**  
30 – 45 sec (on deflation)  
15 – 30 sec – Sure BP (on inflation)

**Standard Cuff Sizes:** Neonate #1 – #5, Infant, Small Child, Small Adult, Adult Long, Large Adult, Thigh

## Default Cuff Inflation Pressure:

Adults: 160 mmHg  
Pediatrics: 120 mmHg  
Neonates: 90 mmHg  
Pressure Measurement Range:  
Systolic: 20 – 260 mmHg  
Diastolic: 10 – 220 mmHg  
Mean: 13 – 230 mmHg  
Maximum Cuff Inflation Pressure:  
Adults: 270 mmHg  
Pediatrics: 170 mmHg  
Neonates: 130 mmHg

## EtCO<sub>2</sub>

**Range:**  
0 – 150 mmHg  
**Accuracy:**  
0 – 38: ± 2 mmHg  
39 – 150: ± 5% + .08% mmHg >38  
**Respiration Range:** 0 – 149 breaths per minute  
**Respiration Rate Accuracy:**  
0 – 70 bpm ± 1 bpm  
71 – 120 bpm ± 2 bpm  
121 – 149 bpm ± 3 bpm  
**Flow rate:** 50 ml/min -7.5 + 15 ml/min  
**Typical response time:** 2.9 seconds  
**Maximum response time:** 3.9 seconds

## Impedance Pneumography

**Displayed Data:** Numeric breath rate, Impedance waveform  
**Breath Rate Range:** Adult, Pediatric: 2 to 150 breaths/minute. Neonates: 3 to 150 breaths/minute.  
**Breath Rate Accuracy:** 2% or ± 2, whichever is greater  
**Displayed Breath Rate:** Average of last 10 breath-to-breath rates

## Leads:

Lead I (RA – LA), Lead II (RA – LL)  
**Sweep Speed:** 3, 13, 6.25, 12.5 mm/sec  
**Alarm Settings:** High, low, and no breath rate alarm

## Invasive Pressure

### Three Channels

**Pressure Range:** -30 – 300 mmHg  
**Pulse Rate Measurement Range:** 25 – 250 bpm  
**Formats:** S/D, S/D (M), (M) user selectable  
**User-Selectable Labels:** P1, P2, P3, ABP, AO, ART, CVP, BAP, FAP, LAP, PAP, RAP, UAP, UVP, ICP  
**Transducer Requirements:**  
5M µV/V/mmHg  
**Zero Adjustment:** ± 200 mmHg  
**Numeric Pressure Accuracy:** ± 2 mmHg or 2% reading, whichever is greater of reading, plus transducer error  
**Transducer Connector:** Standard 6-pin AAMI

## Temperature

Two YSI 400/700 series-compatible channels  
**Range:** 0 – 50°C (32 – 122°F)  
**Units:** °C or °F  
**Display:** T1, T2, and Delta temp  
**Accuracy:** ± 0.1°C (± 0.06°F) from 10 – 50°C (50 – 122°F) ± 0.2°C (± 0.11°F) from 0 – 10°C (32 – 50°F)

## Printer

**Type:** High-resolution thermal array  
**Annotation:** Time, date, ECG lead, ECG gain, heart rate, defibrillation, and pacing parameters and treatment summary events  
**Paper Width:** 80 mm  
**Paper Speed:** 25 mm/sec, 50 mm/sec  
**Delay:** 6 seconds  
**Frequency Response:** Automatically set to monitor's frequency response  
**Record Modes:** Manual and automatic (user configurable)  
**Print Option** Single waveform or a combination up to 3, on alarm, snapshots, treatment summary report, and trend summary

## Battery

**Type:** Rechargeable lithium-ion, 11.1 Vdc, 6.6 Ah, 73 Wh  
**Capacity:** With a new, fully charged battery operating at room temperature: At least 6 hours of continuous monitoring of ECG, SpO<sub>2</sub>, CO<sub>2</sub>, 3 invasive pressure channels, and 2 channels of temperature, with NIBP measurements every 15 minutes and 10 200-joule shocks. 300 shocks at 200 joules with fully charged new battery at room temperature. At least 3.5 hours pacing, with ECG, SpO<sub>2</sub>, CO<sub>2</sub>, three invasive pressures, temperature, NIBP every 15 minutes and pacing at 180 ppm, and 140 mA.  
**AC Power Adapter:** 100 – 240 VAC 50, 60 Hz, 2A 100 – 115 VAC 400Hz, 2A

**ADVANCING  
RESUSCITATION.  
TODAY.®**

ZOLL Medical Corporation  
Worldwide Headquarters  
269 Mill Road  
Chelmsford, MA 01824  
978-421-9655  
800-348-9011  
www.zoll.com

For subsidiary addresses and fax numbers, as well as other global locations, please go to [www.zoll.com/contacts](http://www.zoll.com/contacts).



\*Some capabilities will be available in future releases of compatible software

This product is not available for distribution in the United States or Canada as it has not been reviewed and cleared by the FDA and/or Health Canada.

Specifications subject to change without notice.

© 2012 ZOLL Medical Corporation. "Advancing Resuscitation. Today.", CPR Dashboard, Rectilinear Biphasic, Real CPR Help, RescueNet, See-Thru CPR, X Series, and ZOLL are trademarks or registered trademarks of ZOLL Medical Corporation in the United States and/or other countries. Propaq, Smartcuf, and Sure BP are registered trademarks of Welch Allyn. Masimo, Rainbow, SET, SpCO, and SpMet are trademarks or registered trademarks of Masimo Corporation. All other trademarks are the property of their respective owners.

Printed in U.S.A. 021210 9656-0235-05

**ZOLL®**