

Banner Decal **INSTALLATION INSTRUCTIONS**

STEP 1: Choose a location

Visualz decal banners adhere well to smooth, indoor surfaces. **You want to choose a RECOMMENDED surface.**

Recommended Surfaces:

- Smooth walls
- Painted drywall
- Glass
- Metal
- Sanded wood (without lacquer)
- Inside, temperature controlled environments

NOT Recommended Surfaces:

- Freshly painted walls. Wait 30 days after painting before you put up your Visualz decal banner.
- Textured walls
- Unpainted drywall
- Brick
- Cinder block
- Porous, textured paneling
- Vehicles
- Outside, non-temperature controlled environments

STEP 2: Measure

Measure your space to make sure the decal banner will fit. Visualz decal banners measure 24" x 63".

STEP 3: Unwind

Unwind the banner and lay flat for an hour prior to application.

STEP 4: Clean the wall

Visualz decal banners require a clean wall for a good application. Use a warm, damp cloth to wipe down the surface and let it dry completely. **DO NOT** use soap or cleaning agents, which can make your decal stick poorly.

STEP 5: Find help

Find someone to help you with the installation to help avoid having the decal banner stick to itself once the backing is peeled off.

STEP 6: Stick it to the wall

With help from a friend, start at the top of your Visualz decal banner and carefully peel it from its backing. Place one corner on the wall and slowly smooth the rest into place using minimal pressure. If you make a mistake, gently peel the decal off the wall and reposition it.

To get any air bubbles out, start from the middle of your decal banner and push out to the edges with a squeegee, piece of cardboard, or a credit card. Keep the backing in case you want to move your decal to a new location.

Visualz decal banners are repositionable up to 2-3 times before the adhesive loses tackiness.