

BA-5590 Battery Box

The high capacity **BA-5590 Battery Boxes** are designed to supply 15 VDC output from the standard and new high-capacity BA-5590 military batteries. The Battery box will also accept a 15 VDC input, which transforms a single input to 3ea – 15 VDC outputs. Battery boxes come in a 5 & 10 battery configuration. Both model Battery Boxes can be configured to a 15VDC or 30VDC output.



Part #: TSE-5590-BX-5



New Side Panel View



Part #: TSE-5590-BX-10

Specifications

Power Configurations	5ea or 10ea Battery Case
Power Output	15VDC – Standard or 30VDC – Optional
Capacitance	5 – 70Ah, 10 – 140Ah (15 VDC Configuration)
Battery Compatibility	BA-5557, BA-5590, BA-5390, BB-590, BB-390, BB-2590
Power Output Connectors	2ea Female 2-Pin Tajimi & 2ea Female 2-Pin Amphenol
Voltage Output	Same as input from battery, wired for 12V nominal
Weight	32 lbs. for 10-battery capacity box (10 lbs. without batteries) 18 lbs. for 5-battery capacity box (7 lbs. without batteries)
Operating Temperature	-30°C to 60°C
Storage Temperature	-40°C to 70°C
Dimensions	13 ½" W x 6" H x 12.25" D for 5-battery capacity box 16 ¼" W x 7" D x 13 ¼" D for 10-battery capacity box
Optional Connector Configurations	Available with military or non-standard power connectors

Available on GSA Schedule **GS-35F-0039T**

Tactical Support Equipment Inc.
4039 Barefoot Road
Fayetteville, NC 28306
www.tserecon.com

For More Information
Contact sales@tserecon.com

Phone: 800.889.4030
Phone: 910.425.3360
Fax: 910.425.3361

