



**39" 12.5Ga Red Brand® Monarch® Field Fence**

<b>Property</b>	<b>Tolerance</b>
Resource No.	70046
Resource Name:	939-6-12.5MR RBFF C1 20R 6/P
Knot Type:	Monarch Hinge Knot
Stay Wire Spacing (inches)	6.0"
Zinc Galvanized Coating:	Class 1
	0.30 oz/ft <sup>2</sup> minimum for 10 ga
	0.28 oz/ft <sup>2</sup> minimum for 12.5 ga
Roll Height (inches)	39"
Roll Length (feet)	330' (20 Rods)
Roll Weight: (pounds)	167
Number of Line Wires	9
Line Wire Spacing (Bottom to Top):	3.0", 3.5", 4.0", 4.5", 5.0", 5.5", 6.0", 7.0"
Top & Bottom Line Wire Diameter:	0.135" ± 0.005" (10 gauge)
Breaking Strength Top/Bottom Line Wire (10 ga):	860 pounds-force minimum
Tensile Strength Top/Bottom Line Wire (10 ga):	60,000 psi minimum
Filler Line & Stay Wire Diameter:	0.099" ± 0.005" (12.5 gauge)
Breaking Strength Filler Line & Stay Wire (12.5 ga.):	460 pounds-force minimum
Tensile Strength Filler Line & Stay Wire (12.5 ga.):	60,000 psi minimum
Number of Stays Per Roll	661
Rolls Per Pallet	6
Applicable Specifications	ASTM A116
Mill Test Certificates	No

This product is designed to meet the requirements of ASTM A116. It is produced from steel that has been melted, cast, rolled, drawn, galvanized and fabricated by Keystone Steel & Wire, Peoria, IL. It conforms to the requirements of Buy America.

Made in USA.