



**Product Specification**  
**King Ranch® Fence**  
**949-12-9SD KRF C3 20R**

<u>Property</u>	<u>Tolerance</u>
Resource No.:	70230
Resource Description:	Heavy-Duty Woven Field Fence
Roll Weight:	288 pounds
Knot Type:	Square Deal® fixed knot with continuous stays
Roll Length:	330 feet (20 Rods)
Roll Height:	49 inches
Number of Line Wires:	9
Number of Vertical Stay Wires:	331
Breaking Strength Line Wire and Bottom Cable (9 ga.):	1500 pounds-force minimum
Breaking Strength Top Cable (6 ga.):	2400 pounds-force minimum
Stay, Intermediate Line and Bottom Cable Wire Diameter:	0.1483 ± 0.005" (9 gauge)
Top Cable Wire Diameter:	0.192 ± 0.005" (6 gauge)
Zinc Galvanized Coating:	Class 3 0.90 oz/ft <sup>2</sup> minimum for 9.0 ga 1.00 oz/ft <sup>2</sup> minimum for 6.0 ga
Wire Spacing:	12" between verticals
Variable horizontal bottom to top:	5.5", 5.5", 5.5", 5.5", 5.5", 5.5", 8.0", 8.0"

The King Ranch® Fence provides valuable livestock with a full 49" of protection. Features variable vertical spacing, Class 3 galvanized coating for extra durability, and the exclusive Red Brand Square Deal® Knot. Exclusive knot design eliminates sagging and helps keep fence taut and upright. Designed originally for the King Ranch in Texas, this product is a special construction that conforms to the requirements of ASTM A116 and ASTM A641 for Type Z, Class 3 woven field fence.

Made in USA.

Keystone Steel & Wire  
 Technical Services  
 Peoria, IL 61641-0002  
 September 25, 2008  
 Rev. 1