7000 South West Adams Peoria, IL 61641-0002 (309)697-7020 Fax (309) 697-7487 www.Keystonesteel.com



## Product Specification King Ranch® Fence 949-12-9SD KRF C3 40R

<u>Property</u> <u>Tolerance</u>

Resource No.: 70233

Resource Description: | Heavy-Duty Woven Field Fence

Roll Weight: | 581 pounds

Knot Type: | Square Deal® fixed knot with continuous

stays

Roll Length: 660 feet (40 Rods)

Roll Height: 49 inches

Number of Line Wires: 9

Number of Vertical Stay Wires: 661

Breaking Strength Line Wire and Bottom Cable (9 ga.): 1500 pounds-force minimum

Breaking Strength Top Cable (6 ga): 2400 pounds-force minimum Stay, Intermediate Line and Bottom Cable Wire Diameter: 0.1483 ± 0.005" (9 gauge)

Top Cable Wire Diameter:  $0.192 \pm 0.005$ " (6 gauge)

Zinc Galvanized Coating: Class 3

0.90 oz/ft² minimum for 9.0 ga

1.00 oz/ft<sup>2</sup> minimum for 6.0 ga

Wire Spacing: | 12" between verticals

Variable horizontal bottom to top: | 5.5", 5.5", 5.5", 5.5", 5.5", 5.5", 8.0", 8.0"

The King Ranch® Fence provides valuable livestock with a full 49" of protection. Features variable vertical spacing, Class 3 galvanized coating for extra durability, and the exclusive Red Brand Square Deal® Knot. Exclusive knot design eliminates sagging and helps keep fence taut and upright. Designed originally for the King Ranch in Texas, this product is a special construction that conforms to the requirements of ASTM A116 and ASTM A641 for Type Z, Class 3 woven field fence.

Made in USA.

Keystone Steel & Wire Technical Services Peoria, IL 61641-0002 September 25, 2008 Rev. 1