

7000 South West Adams
 Peoria, IL 61641-0002
 (309)697-7020
 Fax (309) 697-7487
 www.Keystonesteel.com



48" 12.5 Ga Red Brand® Non-Climb Black Painted Horse Fence

Property	Tolerance
Resource No.	70386
Resource Name:	1348-2-12.5NC BLK C1 100' 8/P
Knot Type:	Square Deal Fixed Knot
Stay Wire Spacing (inches)	2.0"
Zinc Galvanized Coating:	Class 1
	0.30 oz/ft ² minimum for 10 ga
	0.28 oz/ft ² minimum for 12.5 ga
Paint	Black Water Based
Roll Height (inches)	48
Roll Length (feet)	100'
Roll Weight: (pounds)	121
Number of Line Wires	13
Line Wire Spacing (horizontal):	4"
Top & Bottom Line Wire Diameter:	0.135" ± 0.005" (10 gauge)
Breaking Strength Top & Bottom Line Wire (10 ga):	860 pounds-force minimum
Tensile Strength Top & Bottom Line Wire (10 ga):	60,000 psi minimum
Filler Line & Stay Wire Diameter:	0.099 ± 0.005" (12.5 gauge)
Breaking Strength Filler Line & Stay Wire (12.5 ga.):	460 pounds-force minimum
Tensile Strength Filler Line & Stay Wire (12.5 ga.):	60,000 psi minimum
Number of Stays Per Roll	601
Rolls Per Pallet	8
Applicable Specifications	ASTM A116
Mill Test Certificates	No

This product is designed to meet the requirements of ASTM A116. It is produced from steel that has been melted, cast, rolled, drawn, galvanized and fabricated by Keystone Steel & Wire, Peoria, IL. It conforms to the requirements of Buy America.

Made in USA.