

There is Power Mobility. And then there's

POWERFUL MOBILITY



Gypsy



There is Power Mobility. And then there's

POWERFUL MOBILITY

Gypsy

The Gypsy is the lightest scooter in the industry with a total weight of 37 lbs, including battery. Patented in the U.S., the Gypsy collapses and folds to the size of a carry-on bag, with a driving range of 7 – 10 miles. Battery type/size = 24V 11.6Ah/Lithium-Ion. The Gypsy's weight capacity is 250 lbs. Available in Pearl Green, Ocean Blue, and Gypsy Red.



MAX SPEED
4.0
MPH



LOAD CAPACITY
250
LBS



BATTERY
11.5 Ah
SLA



RANGE
6.3
MILES

Overall Length	36"
Overall Width	16"
Overall Height (at Maximum Tiller Height)	36"
Overall Height – at Minimum Tiller Height	28" / 711mm
Legroom – Floorboard Length x Width	9.6" x 10" / 245x 252mm
Deck Height – Floorboard to Floor	6" / 150mm
Ground Clearance	1.7" / 45mm
Turning Radius	56"
Folded Overall Length	25" / 640mm
Folded Overall Width	16.5" / 420mm
Folded Overall Height	11" / 290mm
Weight with Std.	37 lbs / 16.7 Kg
Battery Weight	4 lbs / 1.85 Kg
Weight without Batteries	33 lbs / 14.96Kg

Seat Type	PU
Seat – Width & Depth & Height	13" x 9" / 330mm x 230mm
Seat – Cushion Thickness	1.2" / 30mm
Seat Height – Cushion to Deck	13.4" / 340mm
Seat Height – Cushion to Floor	19.3" / 490mm
Tire Type	PU Solid
Front Wheel	6.5" X 2 PCS
Rear Wheel	7.5" X 2 PCS
Anti-Tipper Wheels-Rear	NA
Battery Type & Power	11.5AH LITHIUM-ION BATTERY
Tiller Type	T bar
Throttle Control Type	Lever

Brake System	Electromagnetic brake
Climbing Angle – Maximum Recommended	6 degree
Charger Type	2 Amp
Charging Time	8 Hours
Controller	Dynamic 50A
*Driving Range	Up to 8 miles
Load Capacity	250 lbs / 115 Kg
Motor	DC 24V / 180 W / 4700 RMP (1:21)
*Speed – Maximum	4 mph / 6.4 Km/h
Colors	Gypsy Red / Blue / Pearl Green / Silver

(*) SPECIFICATION PERFORMANCE IS DETERMINED IN THE LABORATORY SETTING BASED ON IDEAL CONDITIONS (MINIMAL FRICTION, NO WIND AND CONTROLLED TEMPERATURE AND PRESSURE WITH AN AVERAGE STANDARD WEIGHT). ACTUAL PERFORMANCE WILL BE DIFFERENT THAN RESULTS OBTAINED DURING LABORATORY TESTING.