



SPECIFICATIONS

Model: F330

Charging Protocols:

Type C: PD3.0, PPS, QC2.0-4.0, Apple, FCP, SCP, AFC, SFCP, PE

Input: AC 100V-240V 50-60Hz

Output Type-C1/C2: Max 100W 5V=3A / 9V=3A / 12V=3A / 15V=3A / 20V=3A / 20V=5A / 5V=4.5A / 4.5V=5A

Output DC: Max 330W 20V=16.5A

Size: 4.97x3.54x1.37inch / 126.5x90x35mm

Weight: 19.7oz /560g

Operating Temperature: 32°F-104°F/0-40°C

POWER ALLOCATION

The total output of the charger is 330W. It supports any usage from each and all the 3 ports, as long as the total is within 330W. When the actual load on the charger exceeds 330W, the charger will be overloaded and it will reset or shutoff. You need to disconnect device(s) from it to reduce the charging load so the charger can work normally.

The charger comes with multiple safety features including input & output over current protection, over-voltage protection, over-temperature protection, overload protection, short circuit protection, electric surge protection, leakage protection, anti-electromagnetic protection, anti-ripple, and ESD protection.

PACKING LIST



SlimQ F330 Charger x1



1.5M AC Cable(C6) x1

Choose from
US/UK/EU/AU



1.5M DC Cable x1
XT60 to 5.5x2.5mm



User Guide x1

NOTE: Please do not use the adapter for devices over 330W. The adapter may get hot or damaged if used over capacity. If you have to use the adapter for such devices, you are at your own risk and any damage caused by such improper use is not covered in the warranty.

