

## License Plate Light Install Instructions (Part #: 69270-XX)

PARTS / TOOLS NEEDED:			
	Affix with screws appropriate in length and thread for the mounting surface. Lamp mounting features sized for #6, or #8 pan head screws.	Power Drill	Butt Splices & Application Specific Sealant
License Plate Light	Not Provided	Not Provided	Not Provided

## **Safety Instructions**


- Disconnect power before installing, adding or changing any component.
- To avoid a hazard to children, account for all parts and destroy all packing materials.
- Do not install any luminaire assembly closer than 6" from any combustible materials.
- Positive (+) outputs require a fuse if the attached wire leads are not rated to handle the max current.
- \*\*DOT: 8 Lux min on plate. Light must be mounted 3-4" to the side of license plate.



1. Determine the installation location drill a hole for the wires then align the light in the wire hole and use the light to mark screw holes. Drill appropiate sized holes for mounting screws.



**2.** Follow the wiring diagram below to wire the light to your system.



3. Feed the wires back through the hole and use application specific sealant around wire hole.



**4.** Screw the light in place using the screws provided.



For warranty information please visit www.itc-us.com 3030 Corporate Grove Dr • Hudsonville • MI • 49426

Phone: 616-396-1355 • www.itc-us.com • sales@itc-us.com • DOC#: 710-00159 • Rev A: 01.16.20