

Light Weight Belting Specification Sheet

Catalog #2BItem number:4183Description:4183IWP 140 3/32in Red Urethane >International Designation:EM24/M UO/U24 Red	35	Pulley Diameter, Minimum B A) Normal Flex	n (100.00 mm) 3.9370 in		
		B) Back Flex	(200.00 mm) 7.8740 in		
Construction:					
Compound Top Cover	Red PU	Belt Strength:			
Top Cover Thickness (in)	(2.40 mm) 0.0945 in	Pull for 1% Elongation	(25 N/mm) 140 lbs/sq in		
Top Cover Description	Gloss		(,		
Top Cover Shore	92	Splice Instructions:			
Compound Bottom Cover	Solid Woven	Foil	Yes		
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in	Splice Process	Finger		
Bottom Cover Description	Friction Surface	Press Temperature (°F)	320 °F		
Bottom Cover Shore	N/A	Press Pressure (psi)	25 lbs/sq in		
Number of Plies	1		ed above is a guideline only. Every vulcanizer is different and will		
Anti Static	No	show different results. We recommend press before attempting the actual belt			
Overall Gauge (in)	(5.00 mm) 0.1969 in		-		
Unit Weight- Ib/PIW	0.0916 lbs/PIW	Others			
Material Between Plies	PU	Other:			
Maximum Width (in)	118	Cross Rigid	No		
Temperature Range (°F)- High	176 °F		No		
Temperature Range (°F)- Low	5 °F	Impression Top Oil Resistant	Yes		
		Fire Resistant	Yes		
		FDA Approved	No		
			NO		

Special Characteristics:

The 2B15 is an excellent choice for tough applications found in recycling and metal stamping plants. The 92 Shore A PU cover is cut and gouge resistant.

*****All Values are nominal and subject to change without notice.*****

St. Louis Branch	Philadelphia Branch	Charlotte Branch	Texas Branch	Boise Branch	Sacramento Branch	Portland Branch	Beltservice Canada Co.	Beltservice de México
St. Louis, MO	Langhorne, PA	Charlotte, NC	Grand Prairie, TX	Boise, ID	Sacramento, CA	Portland, OR	Mississauga, ON	Mexico (ity, Mexico
(800) 727-2358	(800) 777-1314	(800) 849-2358	(800) 727-2358	(800) 423-4469	(800) 289-2358	(800) 347-9251	(877) 210-7423	(5255) 5362-0434
Fax: (314) 344-8511	Fax: (215) 295-5810	Fax: (704) 949-2104	Fax: (314) 314-8511	Fax: (208) 343-8043	Fax: (916) 419-0173	Fax: (503) 285-5380	Fax: (905) 565-9224	Fax: (5255) 5362-0261
NBA National Industrial Belting Association								