



NORTHERN BREWER

MINI KEG SYSTEM

Small and mighty. The Mini Keg System with Snap Tap packs the power of a taproom into a portable, compact 1.75 gallon barrel.

KIT INCLUDES



1.75 Gallon Mini-Keg



Snap Tap



Gas Ball Lock
Disconnect



Mini CO₂
Regulator



CO₂ 2-Pack Cartridge, 74g

ASSEMBLY

1. Thread the gas ball lock disconnect into the brass port on the side of the regulator. Hand-tighten only.
2. Set the regulator in the "OFF" position by turning the dial counter-clockwise until it stops and the word "OFF" is directly over the readout in the front of the regulator.
3. Thread the CO₂ cartridge into the bottom of the regulator. Hand-tighten only.

USE

1. Ensure lid is securely latched on full keg.
2. Attach your regulator assembly to the keg post marked "IN" and turn the dial on the regulator until it displays 12 psi.
3. Pull the pressure-release valve in the center of the lid to the count of two. Wait ten seconds and repeat.
4. Your mini-keg is now purged and ready to carbonate!
5. Refrigerate your mini-keg, with the regulator still attached and set to 12 PSI. The beer will slowly carbonate over the next 7 - 10 days.
6. Once carbonated, attach the Snap Tap™ assembly to the keg post marked "OUT".
7. To pour, fully pull open the plastic faucet tap handle and fill your favorite glass. Check the carbonation level. If the beer is not fully carbonated, allow it to sit for another 24 hours. If the beer is over-carbonated, reduce the regulator pressure slightly and pull the pressure relief valve once to relieve some of the pressure in the keg. The carbonation will stabilize over time.

NOTE: Carbonation level will vary with temperature and with the style of beer. The perfect pour may require slight adjustments to the regulator pressure until the correct balance is achieved. You should not need to exceed 15 PSI to achieve proper carbonation in most cases.

BEFORE YOU BEGIN

Before you can begin serving beer, first thoroughly clean out and sanitize the mini-keg. Add your finished beer to the mini-keg and refrigerate until well chilled.

CARE

When the keg is emptied, detach all fittings and rinse thoroughly with warm water to remove any residual beer. Clean with PBW, or your favorite cleaner after each use. Sanitize thoroughly before each use.

CAUTION! DO NOT DETACH THE CO₂ CARTRIDGE FROM THE REGULATOR UNTIL IT IS COMPLETELY EMPTY.