

Acura TL 2004-2008

AC-54-08-G3



PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and 2 small holes is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Phillips Screw Driver

PARTS INCLUDED: VSM G3, A Plate, J Stem

LOCATION: Right of Radio

STEP 1. Identify the long trim piece that sits to the right of the radio and runs down to the floor console to the right of the emergency brake. Remove this trim piece by placing the DTRT in the space between the trim piece and the floor console behind the emergency brake. From that point, use a gentle twisting motion to release the nine (9) retainer clips that secure this trim piece. Once the retainer clips have been released, place the trim piece off to the side.

Note: The retainer clips are held in very tight; be very cautious not to bend or break the trim piece when releasing the retainer clips.


STEP 2. Locate and remove the Phillips screw directly to the right of the CD player as pictured in picture two (2). Place the VSM G3 in place as pictured, replace the screw and tighten until the mount is secure and flush.

STEP 3. With the mount secure, carefully replace the trim piece you have removed back in its original position. You have successfully installed your VSM G3.

Note: See the Assembly Instructions for G3 Components for additional information.








Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this VSM G3^{1M}.

Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335

Eagandale Court, Eagan, MN 55121, Ph: 651.688.3588 or 800.388.0073 Fx: 651.688.9876



View Instruction & Updates Online at www.pro-fit-intl.com