



**Buick Lucerne (2006-2009)**

**PART NUMBER: BK-53-06-L**



**PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS Pro.Fit Legend.**

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

**TOOLS REQUIRED:** Dash Trim Removal Tool (DM-40-22), 7 mm socket and driver, 5/64" drill bit and drill

**PARTS INCLUDED:** Pro.Fit Legend, instructions, two (2) # 8 x 1/2" screws

**LOCATION:** Right of radio

### STEP 1.

Insert the dash trim removal tool behind the upper-right hand corner of the trim bezel that surrounds the radio. Gently pry trim tool to release a retainer clip. Work the tool around the bezel until it is released. Set bezel aside. **Photo 1.**



### STEP 2.

Remove a 7 mm bolt from both sides of the climate control. Slide the climate control out of the dash, disconnect the wiring and set aside. Remove two (2) 7 mm bolts from each side of the radio. Pull the radio out of the dash, wrap in protective cloth and let hang down. **DO NOT DISCONNECT** the wiring.



### STEP 3.

Place the Legend VSM against the dash pad, right of the radio. Align the bottom of the Legend to where the small ridge starts to curve. **Photo 2.** Using the Legend as a guide, mark the location of two (2) screw holes. Set Legend aside. Drill two (2) pilot holes at the marked location using a 5/64" drill bit and drill. Align the Legend over the pilot holes, insert two (2) # 8 x 1/2" screws and tighten.



### STEP 4.

Re-assemble the dash in reverse order. This completes the installation of your Legend.

Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Pro.Fit Legend. Pro.Fit may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651-688-3588 or 800-388-0073 Fx: 651-688-9876

