



GMC Acadia (2017-2019)



CV-55-08-G3

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Phillips screw driver, 9/32 Socket

PARTS INCLUDED: VSM G3, Lock Plate, J Stem, two 8x1/2 screws

LOCATION: Bottom Right of Climate Control

Step 1: Using a DTRT remove radio screen bezel.

Step 2: Remove the four 9/32 screw bolts holding radio and climate controls. Once removed, pull around the edge of the unit pop loose the unit and position out of the way. No need to disconnect any wires.

Step 3: Position G3 mount on the right-side of the top left bolt screw mounting location. The G3 mounts angles and bends will follow the line of the dash vs being square and tight to the bolt screw location. Mark G3 screw locations or by using cordless screwdriver screw in the 2 #8 screws provided.

Step 4: Reverse steps 2 and 1.



Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1st Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

[View Instructions &
Updates Online at
www.pro-fit-intl.com](http://www.pro-fit-intl.com)