



**Dodge Magnum 2004-2007
Dodge Charger 2004-2007
Chrysler 300 C 2004-2007**



PART NUMBER: DG-51-04-G3

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

**When properly installed, the metal between the ball and 2 small holes is all that is exposed.
(Some exceptions apply).**

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), 5/64" drill bit and drill, #2 Phillips screwdriver, marking pen

PARTS INCLUDED: VSM G3, A Plate, J Stem, three (3) #8x1/2" screws.

LOCATION: Right of Radio

STEP 1. Set the parking brake and put gear shift into low. Insert the DTRT behind the upper right corner of the bezel that surrounds the air vents. Gently pry outward to release a retainer clip. Work the DTRT around the bezel, releasing all the clips. Disconnect bezel wiring and set bezel aside.

STEP 2. Remove four (4) screws that hold the radio in place. There are two (2) on each side of radio. Slide the radio out of its cavity without disconnecting any wiring. Wrap the radio in a protective cloth to prevent scratches and let it hang down.

STEP 3. Align the VSM G3 to the right of the radio as in Photo 2. Using the G3 as a guide, mark the location of three (3) screw holes. Set VSM G3 aside. Drill three (3) pilot holes at the marked location using a 5/64" drill bit and drill. Align the VSM G3 over the pilot holes, insert three (3) #8 x 1/2" screws and tighten.

STEP 4. Re-assemble the dash in reverse order. Remember to reconnect all wiring. This completes the installation of your VSM G3.

Note: See the Assembly Instructions for G3 Components for additional information.



Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this VSM G3™. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651.688.3588 or 800.388.0073 Fx: 651.688.9876

Installation Difficulty

 Simple Advanced

© Pro.Fit International, Eagan, MN 2008

[View Instruction & Updates Online at www.pro-fit-intl.com](#)