

Dodge Ram 2013-2018 w/Dial Shifter
1500 Classic 2019 w/Dial Shifter
PART NUMBER: DG-53-07-G3

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), T20 hex driver, Cordless Drill with Phillips head tip

PARTS INCLUDED: VSM G3, Lock Plate, J Stem, 2-#8 x 1/2" screws

LOCATION: Right of Radio

Step 1: Remove the 4 T20 screws on the upper side of the dash gauge cluster bezel.

Step 2: Using a DTRT pop the gauge cluster bezel loose and remove.

Step 3: Locate the mount just below the curve of the gauge cluster opening. Mark the 2 screw holes to drill pilot holes or using the cordless drill with Phillips head tip to screw in the 2 screws provided.

Step 4: Reverse steps 2 and 1.



Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1st Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

[View Instructions &
Updates Online at
www.pro-fit-intl.com](http://www.pro-fit-intl.com)