



Chrysler Sebring 2007-2010

PART NUMBER: DG-54-08-G3



PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and 2 small holes is all that is exposed.
(Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), T20 Torque bit and driver, 5/64" drill bit and drill, Phillips screw driver, marking pen

PARTS INCLUDED: VSM G3, two (2) # 8 x 1/2" screws, A Plate, J Stem

LOCATION: Right of radio

STEP 1. Insert the DTRT in the lower left hand corner of the dash bezel surrounding the radio and clock. With a gentle twisting motion, release the lower right hand corner of the bezel working your way around the bezel in a counter clockwise rotation until all four (4) clips have been released. Disconnect the wiring and set the bezel carefully aside.

STEP 2. Use a T20 torque bit to remove the four (4) torque screws securing the radio in place. Once the torque screws have been removed, gently pull the radio out, disconnect the wiring and set aside.

STEP 3. Place the VSM G3 in the mounting location as pictured in Photo two (2). When the VSM G3 is flush to the dash and in place, use a marking pen and the VSM G3 as a guide to mark the locations of the pilot holes. Use a 5/64" drill bit and drill to carefully drill the pilot holes. Place the G3 over the pilot holes and secure it flush to the dash using the two (2) provided # 8 x 1/2" screws.

Step 4. Begin to place the dash back together in the reverse order in which it was dismantled. You have successfully installed your VSM G3!

Note: See the Assembly Instructions for G3 Components for additional information.



Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this VSM G3™. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651.688.3588 or 800.388.0073 Fx: 651.688.9876

Installation Difficulty
● ● ○ ○ ○
Simple Advanced

© Pro.Fit International, Eagan, MN 2008

View Instruction & Updates
Online at
www.pro-fit-intl.com