



Dodge Dakota (2005-2007)



PART NUMBER: DG-71-05-L

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS Pro.Fit Legend.

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

TOOLS REQUIRED: #2 Phillips screwdriver, Dash Trim Removal Tool (DM-40-22), 7mm nut driver, 5/64" drill bit and drill

PARTS INCLUDED: Pro.Fit Legend, instructions, two (2) #8 x 1/2" screws

LOCATION: Right of radio

STEP 1.

Locate and remove two (2) 7mm screws at the bottom of the radio bezel, below the air bag switch. **Photo 1.** Insert the dash trim removal tool behind the lower-right corner of the radio bezel. Pry bezel outward to release a retainer clip. Work the trim tool counter-clockwise around the bezel until all clips are released. Disconnect wiring from bezel and set bezel aside.



STEP 2.


Align the top of the Pro.Fit Legend with the top of the radio. **Photo 2.** Using the Legend as a guide, mark the location of two (2) screw holes. Set Legend aside. Drill two (2) pilot holes at the marked location using a 5/64" drill bit and drill. Align the Legend over the pilot holes, insert two (2) # 8 x 1/2" screws and tighten.



STEP 3. Re-assemble the dash in reverse order. This completes the installation of your Legend.



Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Pro.Fit Legend™. Pro.Fit may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651-688-3588 or 800-388-0073 Fx: 651-688-9876



© Pro.Fit International, Eagan, MN 2006

VIEW INSTRUCTIONS & UPDATES
ONLINE @
WWW.PRO-FIT-INTL.COM