

Ford 500 (2005-06)

PART NUMBER: FO-60-05-L



PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS Pro.Fit Legend.

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

TOOLS REQUIRED: Dash Trim Removal Tool (DM-40-22), 7mm nut driver

PARTS INCLUDED: Pro.Fit Legend, instructions, hardware pack


LOCATION: Right of radio

STEP 1. Set parking brake and place gear shift into low gear. Open arm rest console door. Insert dash trim removal tool behind lower right corner of metallic ring around gear shift. Press downward, releasing a retainer clip. Work tool around ring, pressing downward until ring is free. Set ring aside.

STEP 2. The large bezel around gear shift is removed next. Insert trim tool behind back-right corner of the bezel that is normally covered by the console door. Press downward to release a clip. There are four (4) clips on either side of the bezel. When all clips are released, lift bezel over shift and set aside. There are four (4), 7mm screws directly below the climate control bezel. Photo 1. Remove the two (2) 7mm screws in the center.

STEP 3. Insert the trim tool behind the lower-right corner of the radio / climate control bezel. Push downward to release clip. Work tool around bezel until it is free. Let bezel hang down. Do not disconnect any wiring. Remove two (2) 7mm screws from right of radio. Photo 2.

STEP 4. Align Legend over radio screw holes. Insert factory screws and tighten. Re-assemble the dash in reverse order. This completes the installation of your Legend.







Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Pro.Fit Legend. Pro.Fit may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651-688-3588 or 800-388-0073 Fx: 651-688-9876

