

Jeep Wrangler JL 2018-2019

PART NUMBER: FO-61-05-L

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM Legend

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Phillips Screwdriver

PARTS INCLUDED: VSM Legend

LOCATION: Top Left of Radio

Step 1: Use the DTRT to remove the bezel with radio and climate controls. There are clips that hold this on. (Photo #1)

Step 2: Remove the 2 screws that hold the radio screen bezel. And then remove the bezel. The top is held on with clips. (Photo #1)

Step 3: Remove the screw in the upper right corner of the radio and just loosen the other 3 screws holding radio screen. (Photo #2)

Step 4: Place the Legend mount on back side of the radio mounting tab, lining up the left hole of the mount with the mounting tab screw hole. Place the screw back through the mounting tab and through the Legend mount. Tighten the other 3 screws. Adjust the Legend mount so it covers a minimal amount of the retainer clip slot. Then tighten the screw the remainder. (Photo #2)

Step 5: Reverse step 2 and 1 to reassemble.



Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1st Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

[View Instructions & Updates Online at www.pro-fit-intl.com](#)