

Chevrolet Equinox 2018-2020

PART NUMBER: MV-25-03-G3

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Cordless Drill, Phillips Screw tip, 9/32 Socket and ratchet

PARTS INCLUDED: VSM G3, Lock Plate, J-stem, 3-#4 x 3/8" screws

LOCATION: Right of Radio

Step 1: Using a DTRT remove bezel that runs from the right passenger vent to just left of the gauge cluster. Start at the passenger side and moving towards the driver's side. Do not remove completely as you only need it loose enough to remove screws holding climate controls and radio.

Step 2: Using the 9/32 socket remove the 4 screws holding the climate controls. Remove climate controls but no need to disconnect wires. Remove the 9/32 bolts holding radio unit. These are above where the climate controls were and above hazard button. Using a DTRT pop out the radio unit that is now being held by retainer clips. No need to disconnect.

Step 3: Position the mount in the groove the radio on the right side just below where the groove narrows. Mark screw location holes or by using a cordless drill with a Phillips tip screw in screws provided.

Step 4: reverse steps 2 and 1.



Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1st Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

View Instructions &
Updates Online at
www.pro-fit-intl.com