



Hyundai Sonata (2002-2005)



PART NUMBER: MV-50-03-L

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS Pro.Fit Legend.

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

TOOLS REQUIRED: #2 Phillips screwdriver, drill and 5/64" bit, Dash trim removal tool (DM-40-22), 10mm nut driver, marking pen

PARTS INCLUDED: Pro.Fit Legend, instructions, two (2) # 8 x 1/2" screws.

LOCATION: Right of radio

STEP 1. Insert dash trim tool behind upper-left corner of the air vents and radio trim bezel. **Photo 1.** Pry outward to release a retainer clip. Work your hand and dash tool counter-clockwise around the bezel, pulling out to release all the clips. Disconnect wiring harnesses and set bezel aside.



STEP 2. Place the Legend against the dash and to the right of the radio. Slide the Legend back until it touches and align the top so it is even with the words 'BASS' and 'TREB'. **Photo 2.**



STEP 3. Using the holes in the Legend as a guide, mark pilot holes with marking pen. Set the mount aside. **Carefully** drill pilot holes with 5/64" drill bit and drill. Place the Legend over pilot holes and align holes. Insert provided screws and tighten with # 2 Phillips screwdriver.



STEP 4. Assemble dash in reverse order securing all clips and wiring. This completes the installation of your Pro.Fit Legend.

Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Pro.Fit Legend®. Pro.Fit may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651-688-3588 or 800-388-0073 Fx: 651-688-9876

Installation Difficulty
● ○ ○ ○ ○
Simple Advanced