

Hyundai Elantra (2004-2006)

Page 23

Requestion to the second sec

PART NUMBER: MV-50-03-L

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS Pro.Fit Legend.

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

TOOLS REQUIRED: #2 Phillips screwdriver, drill and 5/64" bit, Dash trim removal tool (DM-40-22), 10mm

nut driver, marking pen

PARTS INCLUDED: Pro.Fit Legend, instructions, two (2) # 8 x 1/2" screws.

LOCATION: Right of radio

STEP 1. Open the ash tray and remove it from its cavity. Remove two (2) Phillips screws from the bottom corners of the ash tray cavity. Remove two (2) screws located directly above the speedometer and tach.


STEP 2. Insert dash trim tool behind dash trim bezel right of the air vent and pry outward to release a retainer clip. **Photo 1.** The bezel extends from left of the speedometer and steering column to right of the radio. Work your hand and dash tool counter-clockwise around the bezel, pulling out to release all the clips. Do not attempt to remove the trim bezel.

STEP 3. Pull the bezel out enough to access area right of the radio. Place the **Legend** against the dash and align the top with the bezel clip hole. **Photo 2.**

STEP 4. Using the holes in the Legend as a guide, mark pilot holes with marking pen. Set the mount aside. **Carefully** drill pilot holes with 5/64" drill bit and drill. Place the Legend over pilot holes and align holes. Insert provided screws and tighten with # 2 Phillips screwdriver.


STEP 5. Assemble dash in reverse order securing all clips and replace the ash tray. This completes the installation of your **Pro.Fit Legend.**







Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this **Pro.Fit Legend®**. **Pro.Fit** may not be held liable for any personal injury resulting from accident or improper installation. **Pro.Fit** International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651-688-3588 or 800-388-0073 Fx: 651-688-9876



VIEW INSTRUCTIONS & UPDATES
ONLINE @
WWW.PRO-FIT-INTL.COM