

Toyota Highlander 2014-2019

PART NUMBER: MV-50-03-L

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM Legend

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Cordless Drill, Phillips head tip, 10mm socket and ratchet w/extension

PARTS INCLUDED: VSM Legend, 2-#4x3/8 screws

LOCATION: Above radio

Step 1: Using a DTRT, remove the bezel that runs from the left of the left radio vent to just below the right passenger sided vent (held with retainer clips). The climate controls are attached to this piece. No need to disconnect the radio or the climate controls.

Step 2: Using a DTRT, remove trim running from right of right radio vent to around the clock on the dash (held with retainer clips). Next, remove the right and left vent next to the radio. Now remove the 4-10mm bolts holding the radio (2 below and 1 on each side of the radio). Pull radio out but no need to disconnect the wires.

Step 3: Locate mount on the right side of the radio and just left of the right radio vent. Mark mount holes or by using cordless drill with Phillips head tip screw in the 2 #4x 3/8 screws provided.

Step 4: Reverse steps 1 and 2.



Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1st Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

View Instructions &
Updates Online at
www.pro-fit-intl.com