

2019 Chevrolet Malibu

PART NUMBER: MZ-58-08-G3

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a driver's seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Electric Screw Driver OR Cordless Drill, Phillips Screw tip, 9/32 Socket

PARTS INCLUDED: VSM G3, Lock Plate, J-stem, #8 x 1/2" screw

LOCATION: Right of Screen

Step 1: Using a DTRT remove bezel that runs from the right passenger vent to just left of the gauge cluster. Start at the passenger side and moving towards the driver's side. Do not disconnect starter button.

Step 2: Remove climate controls but no need to disconnect wires. Remove the 2 9/32 bolts holding radio. These are above where the climate controls were and above hazard button. Behind the radio screen using a DTRT pop out small cover that is cover 2 screws holding the top of the radio. Remove screws. No need to pull radio screen out as retainer clips are now holding it. No need to disconnect it either.

Step 3: Position the mount along the top groove of the right side the radio opening (pic4). Mark back hole and pre-dill pilot hole for screw. Now screw in provided screw.

Step 4: Reverse steps 2 and 1.



Pro.Fit International, Inc. ® may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.

Pro.Fit International, Inc. ® 221 1st Street South, Montgomery, MN 56069, Ph: 507.364.7773 or 800.388.0073

Installation Difficulty



Simple

Advanced

©Pro.Fit International, Inc. Montgomery, Minnesota 2017

View Instructions &
Updates Online at
www.pro-fit-intl.com