



Mazda CX-9 2008-2009



MZ-71-08-G3

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a drivers seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break.

When properly installed, the metal between the ball and 2 small holes is all that is exposed.
(Some exceptions apply).

TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Phillips screwdriver

PARTS INCLUDED: VSM G3, A Plate, J Stem

LOCATION: Right of Air Vents

STEP 1. Identify the trim piece that is located to the right of the radio/climate control bezel. Photo #1. Place the DTRT between this trim piece and the floor console towards the bottom of the trim piece, near the transmission shifter. Use a gentle twisting motion to release a series of four (4) retainer clips, moving the tool upwards as you release the retainer clips. After the clips have been removed, set the trim piece aside.



STEP 2. Remove the Phillips screw located to the right of the air vents. Photo #2. Place the VSM G3 into position as pictured.



STEP 3. Once the VSM G3 is flush and secured to the contours of the dash, replace the trim piece carefully back into position. You have successfully installed your VSM G3.



Note: See the Assembly Instructions for G3 Components for additional information.

Pro.Fit International, Inc.® may not be held liable for any damage to a vehicle before, during or after the installation or removal of this VSM G3™. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation. Pro.Fit International, Inc.® 1335 Eagandale Court, Eagan, MN 55121, Ph: 651.688.3588 or 800.388.0073 Fx: 651.688.9876

Installation Difficulty
● ○ ○ ○ ○
Simple Advanced

© Pro.Fit International, Eagan, MN 2008

View Instruction & Updates
Online at
www.pro-fit-intl.com