Ford F150 2015-2018

PART NUMBER: ST-52-03-L

PLEASE READ COMPLETE INSTRUCTIONS BEFORE INSTALLING THIS VSM G3

All instructions assume a drives seat vantage point. Caution is advised when removing and reassembling wood or plastic parts of a dash. Applying unnecessary force or pressure may cause a piece to crack or break. When properly installed, the metal between the ball and the small hole is all that is exposed. (Some exceptions apply). TOOLS REQUIRED: Dash Trim Removal Tool (DTRT), Electric Drill, Socket Wrench, 9/32 Socket

PARTS INCLUDED: VSM Legend, 3 washers LOCATION: Right of radio

Step 1: Using the DTRT and your hand remove the center dash/speaker cover right above the radio.

Step 2: Remove the 2 nut screws using a 9/32 socket above and to the right and left of the speaker.

Remove the panel with speaker. Unplug speaker and set panel aside. (Photo #1)

Step 3: Remove 2 nut screws using the 9/32 socket. By pulling from the top now, remove the radio trim and controls leaving the screen in place. (Photo #2)

Step 4: Remove the center screw holding the radio screen in place. Place screw through bottom screw hole of the mount (mount point to the right) and place provided washers on the backside of the mount and on screw. Carefully place the mount into position and screw the nut screw back into previous hole. (Photo #3)

Step 5: Putting back on the trim and controls start by putting the mount through the radio screen hole. (You will need to flex mount a little to get trim back into place) Then reverse steps 3 to 1. (Photo #4)



Pro.Fit International, Inc. e may not be held liable for any damage to a vehicle before, during, or after the installation or removal of this VSM G3. Pro.Fit International may not be held liable for any personal injury resulting from accident or improper installation.



View Instructions & Updates Online at www.pro-fit-intl.com

Simple

©Pro.Fit International, Inc. Montgomery, Minnesota 2017